



LED mast light IP66 - Luminaire for streets and places 48 3202



Schuch
48 3202
480010016
4041254261232 EAN/GTIN

41577,47 INR excl. VAT**
plus shipping

 16-17 days* (IND)

LED mast luminaire IP66 48 3202 Type of mounting top-mounted/side-entry, Light source LED not interchangeable, With light source, Housing material aluminium, Housing color gray, Cover material glass transparent, Type of voltage AC, Rated voltage 220... 240V, Control gear LED control gear current-controlled, With Control gear, Without dimming function, Energy efficiency class of the built-in lamp A++, A+, A (LED), Rated service life L80/B50 at 25 °C 100000h, Degree of protection (IP) IP66, Suitable for spigot size 42... 76mm, Impact resistance IK08, Protection class II, Remote control without, max. system power 50W, rated luminous flux according to IEC 62722-2-1 6850lm, light color white, color temperature 4000... 4000K, color rendering index CRI 70-79, width 251mm, height/depth 155mm, length 610mm, LED street light. Two-piece die-cast aluminum housing with smooth surface without external cooling fins, powder-coated metallic gray (DB 702N). Upper part with LED, optics, cover glass and electrical components, can be removed from the lower part for easy and time-saving installation. Lower part with integrated mast fastening system, cable entry, strain relief and pressure equalization system with internal ventilation in the mast connection area (protected against dirt). Inclination angle adjustment 0° to 10° for top mounting, 0° to -15° for side mounting depending on the inclination of the extension arm. Frameless, flat safety glass, impact resistance at least IK08. Disconnect plug connection and strain relief. High-performance LED with highly efficient optics modules, asymmetric wide beam light distribution, direct beam, multi-layer technology. Direct connection of the LED to the housing to ensure optimal thermal management. Electronic ballast, service life 100,000 hours, with overload, short-circuit and overtemperature protection. Surge withstand voltage 10kV. Integrated mast mounting system made of die-cast aluminium, universal for post-top Ø 60/76mm and side-entry Ø 42/60mm by simply folding down the cover flap. Installation is made easier by pre-assembling the lower part of the luminaire on the mast and then putting on the upper part. Protection class II, protection class IP66. High power LED, 4,000K, lifespan 100,000 hours (L80). Luminaire luminous flux 6,390lm, system power 50W, energy efficiency class A++.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

