Item Number
EB15903171

28.03.2024/09:57

https://www.eibabo.in/obo/combicontroller-v50-single-pole-with-npe-fs-combined-arrester-for-power-systems-v50-1-npe-fs-280-eb15903171



CombiController V50 single-pole with NPE+FS - Combined arrester for power systems V50-1+NPE+FS-280

OBO
V50-1+NPE+FS-280
5093531
4012196159703 EAN/GTIN

16890,90 INR excl. VAT**
plus **shipping**

16-17 days* (IND)

CombiController V50 single-pole with NPE+FS V50-1+NPE+FS-280 TN system type, TN-CS system type, TN-S system type, TT system type, number of poles 2, lightning impulse current (10/350 µs) 12.5kA, maximum continuous voltage AC 280V , nominal voltage AC 230V, protection level 1.3kV, protection level LN 1.3kV, protection level N-PE 1.5kV, follow current extinguishing capacity 0.1kA, max. conductor cross-section solid (solid/stranded) 35mm², max. conductor cross-section flexible (finely stranded) 35mm², Mounting type DIN rail TH35, size 2 HP, remote signaling, optical signaling on the device, test class type 1 and 2, The V50 combined lightning current arrester made of halogen-free plastic is suitable for lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305). The modular, pluggable arresters are characterized by a dynamic disconnect device and an optical status display. The FS with NPE variant offers a heavy-duty spark gap between the neutral and protective conductors as well as a potential-free changeover contact that enables remote signaling. The CombiController is particularly suitable for lightning protection equipotential bonding for buildings of lightning protection class III and IV. The lightning current discharge capacity is 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total. The vibration-proof latching and the voltage and type coding ensure safety and avoid mixing up upper and lower parts. The wedge-shaped design of the contacts makes it easy to insert and even easier to remove the upper parts. Additional technical product information can be called up quickly and easily using the QR code on the rating plate using mobile devices.

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

COMPLAINTS HANDLING
Obliging and 100% safely

SHORT DELIVERY TIME
Warehousing

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

25 YEARS OF EXPERIENCE
In worldwide mail order

REFUND
Within 14 days

DHL TRACK & TRACE
Shipment tracking

ORDER LIVE CHAT
With order history

DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).
** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online