

Item Number EB16505855

×

https://www.eibabo.in/merten/knx-outdoor-motion-detector-argus-220-degrees-polar-white-632519-eb1 6505855



KNX outdoor motion detector ARGUS, 220 degrees, polar white 632519

**Merten** 632519 4042811083083 EAN/GTIN

12585,92 INR excl. VAT\*\*

plus shipping



KNX ARGUS 220 pws 632519 KNX bus system, other bus systems without, motion detector design, surface-mounted installation, material plastic, other material quality, surface untreated, surface design matt, color white, RAL number (similar) 9010, with bus coupling, creep-by protection/rear field monitoring, Staircase monitoring, response brightness adjustable, optimum installation height 2.5m, max. range to one side 12m, max. frontal range 16m, detection field diameter on the floor 24m, horizontal detection angle 0 ... 220°, number of channels 20, number of binary inputs 0, Min. switch-on time 1s, max. switch-on time 9144min, KNX motion detector for outdoor use. 220 degree area surveillance for larger house fronts and areas of the house. With integrated bus coupler. The physical address is programmed with a magnet. 360 degree close protection zone (approx. 4 m radius). Large connection space and plug-in system. Looping possible. LED function display for quick alignment at the installation site. Controls are protected under the easily accessible cover plate. Flexibly adjustable sensor head. It is possible to hide individual lens areas. Wall and ceiling mounting without additional accessories. Attachment to outside/inside corners and stationary pipes with a mounting bracket. KNX software functions: Five movement blocks: Up to four functions can be triggered per block. Telegrams: 1 bit, 1 byte, 2 bytes. Normal operation, master, slave, safety pause, locking function. Sensitivity, brightness and staircase lighting time can be set via the ETS or the potentiometer. Learnable staircase lighting timexx detection angle: 220 degrees. Range: max. 16 m. Number of levels: 7. Number of zones: 112 with 448 switching segments. Light sensor: infinitely variable from approx. 3-1000 lux, infinite lux (infinite: motion detection is independent of the ambient brightness). Time: adjustable from outside 1 s to approx. 8 min. in 6 stages or via ETS from approx. 3 s to approx. 152 hours. Sensitivity: continuously adjustable. Wall mount sensor head adjustment: 9 degrees up, 24 degrees down, 12 degrees right/left, +/-12 degrees axial. Sensor Head Adjustment Ceiling Mount: 4 degrees up, 29 degrees down, 25 degrees right/left, +/-8.5 degrees axial. EC directives: Low Voltage Directive 2006/95/EG and EMC Directive 2004/108/EG. Degree of protection: IP 55. Dimensions: 151x93x71 mm (HxWxD). Accessories: mounting bracket 565291/92/93. Programming magnet 639190. Scope of delivery: With cover plate and segments to limit the detection area, screws and dowels. Colour: polar white,

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

