



LED ceiling/wall light 4000K D500 H150 - Ceiling-/wall luminaire 1x21W 211401.002.1



RZB

211401.002.1

4051859075561 EAN/GTIN

22190,48 INR excl. VAT**

plus shipping



16-17 days* (IND)

LED ceiling/wall light 4000K D500 H150 211401.002.1 Energy efficiency class of the supplied replaceable light source A+, Highest energy efficiency class of the replaceable light source A+, Lowest energy efficiency class of the replaceable light source A+, Energy efficiency class range A++ to E, Suitable for wall mounting, Suitable for ceiling mounting, Suitable for surface mounting, Illuminant LED not interchangeable, with illuminant, suitable for VDU workstations according to EN 12464-1, suitable for number of illuminants 1, other socket, material of the housing plastic, housing color white, material of the cover glass opal, version of the grid without, voltage type AC, nominal voltage 220 ... 240V, control gear LED control gear, current-controlled, with control gear, without dimming function, light distributor without, symmetrical light distribution, beam angle unshielded/diffuse, light emission direct/indirect, rated service life L70/B10 at 25 °C 50000h, protection class (IP) IP43, impact-resistant IK03, protection class I, rated ambient temperature according to IEC62722-2-1 25 ... 25°C, glow wire test according to IEC 60695-2-11 960 °C - 30 s, suitable for lamp power 21 ... 21W, max. system power 21W, Rated luminous flux according to IEC 62722-2-1 2200lm, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, luminous efficacy of luminaire 105lm/W, height/depth 150mm, outer diameter 500mm, type of wiring termination, number of poles 3, conductor cross-section 2, 5mm², connection type plug-in terminal, very extensive ceiling and wall light series for interiors. Mouth-blown three-layer opal glass (triplex glass) satin matt. The triplex glass ensures particularly homogeneous, soft and glare-free light. In numerous diameters from 200 to 630 mm. Motion sensor versions available. Optional decorative rings for further customization. Light color 840. Plastic holder. The cover is fastened with a bayonet catch. Cover Glass opal, satin finish, hand-blown. IP43 ceiling mounting, IP44 wall mounting.

YOUR ADVANTAGES



WORLDWIDE TRADE

Corporate video eibmarkt®



99% CUSTOMER SATISFACTION

> 500,000 customers worldwide



DHL TRACK & TRACE

Shipment tracking



COMPLAINTS HANDLING

Obliging and 100% safely



25 YEARS OF EXPERIENCE

In worldwide mail order



ORDER LIVE CHAT

With order history



SHORT DELIVERY TIME

Warehousing



REFUND

Within 14 days



DATA PROTECTION

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

