

Item Number EB11596691

https://www.eibabo.in/zumtobel/led-recessed-ceiling-light-r68-10w827230vvflsmw-downlight-spot-floodlight-panos-evo-60815039-eb11596691



LED recessed ceiling light R68 10W827230VVFLSMW - Downlight/spot/floodlight PANOS EVO #60815039

×

Zumtobel

PANOS EVO #60815039 60815039 4053167129202 EAN/GTIN

11977,56 INR excl. VAT**

plus shipping



16-17 days* (IND)



LED recessed ceiling light R68 10W827230VVFLSMW PANOS EVO 60815039 Suitable for recessed mounting, Suitable for ceiling mounting, Adjustability not adjustable, Light source LED cannot be replaced, With light source, Suitable for number of light sources 1, Socket without, Housing material aluminium, Housing color white, Cover material opal plastic, Type of voltage AC, Rated voltage 220 ... 240V, Control gear LED control gear current-controlled, With control gear, Without dimming function, Reflector without, Light distribution symmetrical, Light emission direct, Rated service life L70/B50 at 25 °C 100000h, Rated service life L80/B50 at 25 °C 66000h, rated service life L90/B50 at 25 °C 33000h, degree of protection (IP) IP20, protection class II, max. system power 10W, light color white, color temperature 2700 ... 2700K, color rendering index CRI 80-89, rated luminous flux according to IEC 62722-2-1 518lm, height/depth 84mm, outer diameter 78mm, installation height/depth 110mm, installation diameter 68mm, glow wire test according to IEC 60695-2-11 850 °C - 30 s, color consistency (McAdam ellipse) SDCM3, LED recessed ceiling light (complete light), "Stable White", highest light quality thanks to specially designed reflector, fitted with: 10 W LED827, VERY WIDEFLOOD -Emission characteristics, reflector: smooth, coated in an aluminum color and matt (52°), color rendering Ra > 80, color temperature 2700 K (warm white), color location tolerance (initial MacAdam): 3, luminous flux of luminaires: 518 lm, luminous efficacy of luminaires: 52 lm/W, Service life: 50000h at 85% luminous flux, with ballast unit, modular, high-quality optical unit made of reflector and LED light chamber, integrated in optimized heat management made of die-cast aluminium, reflector/cover ring made of high-quality, UV-resistant polycarbonate (PC), cover ring white, Mounting ring made of die-cast aluminium, tool-free quick assembly of the lamp unit using a bayonet catch, IP44_IP20, lamp wired without halogen, connection: 2-pole terminal, mains volt

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLING Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTIONGuarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

