

Item Number EB11596736

https://www.eibabo.in/zumtobel/led-recessed-ceiling-light-r100l-11w840230vwhwh-downlight-spot-flood light-panos-evo-60815126-eb11596736



LED recessed ceiling light R100L 11W840230VWHWH - Downlight/spot/floodlight PANOS EVO #60815126

×

Zumtobel

PANOS EVO #60815126 60815126 4053167130093 EAN/GTIN

14102,85 INR excl. VAT**

plus shipping



16-17 days* (IND)



LED recessed ceiling light R100L 11W840230VWHWH PANOS EVO 60815126 Suitable for recessed mounting, Suitable for ceiling mounting, Adjustability not adjustable, Light source LED cannot be replaced, With light source, Suitable for number of light sources 1, Socket without, Housing material aluminium, Housing color white, Cover material opal plastic, Voltage type AC, Rated voltage 220 ... 240V, LED rated current at constant current 53 ... 53mA, Control gear LED control gear, current-controlled, With control gear, Without dimming function, Reflector without, Light distribution symmetrical, Light emission direct, Rated service life L70/B50 at 25 °C 100000h, rated service life L80/B50 at 25 °C 33000h, degree of protection (IP) IP20, impact resistance IK04, protection class II, max. system power 11W, light color white, color temperature 4000 ... 4000K, Color rendering index CRI 80-89, rated luminous flux according to IEC 62722-2-1 970Im, power factor 0.9, height/depth 93mm, outer diam hmesser 113mm, installation height/depth 100mm, installation diameter 100mm, glow wire test according to IEC 60695-2-11 850 °C - 30 s, color consistency (McAdam ellipse) SDCM3, LED recessed ceiling light (complete light), "Stable White", Cut-off angle 60°, fitted with: 11 W LED840, 62°, color rendering Ra > 80, color temperature 4000 K (neutral white), color location tolerance (initial MacAdam): 3, luminous flux of luminaires: 970 Im, luminous efficacy of luminaires: 88 Im/W, service life: 50000h at 85% luminous flux, with ballast unit, modular, high-quality optical unit made of reflector and LED light chamber, integrated in optimized heat management made of die-cast aluminum, smooth reflector painted white, reflector/cover ring made of high-quality, UV-resistant polycarbonate (PC), cover ring white, mounting ring made of glass-fibre reinforced polycarbonate (PC), grey, tool-free rapid assembly of the luminaire unit using a bayonet catch, IP44_IP20, luminaire wired without halogen, connection: 3-pin plug-in connection terminal, looping t

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

