

**LED ceiling/wall light 3000K D460 w.HF-BWM - Ceiling-
/wall luminaire 8x2,2W 311518.002.8.19****RZB**

311518.002.8.19

4051859073901 EAN/GTIN

19102,88 INR excl. VAT**

plus shipping



16-17 days* (IND)

LED ceiling/wall light 3000K D460 m.HF-BWM 311518.002.8.19 Suitable for wall mounting, Suitable for ceiling mounting, Suitable for surface mounting, Light source LED not replaceable, With light source, Suitable for number of light sources 8, Other socket, Housing material Steel, Housing colour white, cover material plastic opal, louvre version without, voltage type AC, nominal voltage 220 ... 240V, control gear LED control gear, current-controlled, with control gear, without dimming function, light distributor without, light distribution symmetrical, beam angle unshielded/diffuse, light emission direct/indirect, Rated service life L80/B10 at 25 °C 50000h, degree of protection (IP) IP40, degree of protection (NEMA) other, impact resistance IK10, protection class I, rated ambient temperature according to IEC62722-2-1 25 ... 25°C, with motion detector, glow wire test according to IEC 60695-2-11 850 °C - 30 s, suitable for lamp power 2.2 ... 2.2W, max. system power 19W, rated luminous flux according to IEC 62722-2-1 215 0lm, light color white, color temperature 3000 ... 3000K, color rendering index CRI 80-89, luminous efficacy of luminaire 114lm/W, power factor 0.95, height/depth 120mm, outer diameter 460mm, type of wiring termination, number of positions 4, conductor cross-section 2.5mm², connection type Plug-in terminal, powder-coated metal bracket. Fastening of the cover with pressure lock. Cover plastic (polycarbonate) opal. With HF motion detector. Parameters of the motion detector at ceiling height of max. 4 m or wall mounting of max. 2.7 m., HF detector 5.8 GHz ISM frequency band, brightness levels: daylight / 300 lux / 150 lux / twilight / darkness / teaching, sensitivity / range 2 m, 10 m diameter (20%, 100%) adjustable, time control approx. 10 seconds to 30 minutes adjustable, detection range 120°, radiated power < 5.0 mW, switching capacity: 800 W (resistive load), 500 W (fluorescent lamp, LED), suitable for outdoor use due to sensitive reaction to all movements

YOUR ADVANTAGES**WORLDWIDE TRADE**

Corporate video eibmarkt®

**99% CUSTOMER SATISFACTION**

> 500,000 customers worldwide

**DHL TRACK & TRACE**

Shipment tracking

**COMPLAINTS HANDLING**

Obliging and 100% safely

**25 YEARS OF EXPERIENCE**

In worldwide mail order

**ORDER LIVE CHAT**

With order history

**SHORT DELIVERY TIME**

Warehousing

**REFUND**

Within 14 days

**DATA PROTECTION**

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

