



Energy meter IEM3365 3P 125A - Direct kilowatt-hour meter 125A A9MEM3365



Schneider Electric
A9MEM3365
3606480696435 EAN/GTIN

28823,78 INR excl. VAT**
plus shipping



16-17 days* (IND)

Energy meter IEM3365 3P 125A A9MEM3365 Electronic meter type, rated current (In) 125A, maximum current (Imax) 125A, rated voltage (Un) NL 100... 277V, rated voltage (Un) LL 480... 480V, frequency 50... 60Hz, accuracy class B, Polart three-wire/four-wire, direct measurement version, active and reactive power energy type, suitable for import/supply, multi-tariff tariff version, internal/external tariff control, Measuring Instruments Directive approval, electrical pulse output, pulse type D0, pulse rate 0... 1000imp/kWh (kvarh), display type digital, mounting type built-in, width in pitch units 7, design of the interface other, number of digits 9, degree of protection (IP) IP20, degree of protection (NEMA) 1, Acti 9 iEM3000 series. iEM3365 energy meter, 3-phase, 11/10, 4 tariffs. Output_K: 1, COM: BAC, Input_K: 1, MID: Yes, max. rated current: 125 A. Three-phase meter for direct measurement up to 125 A. Display: fully graphic LCD display for simultaneous plain text display of menu item/measuring category, measured value, unit and active tariff. Partial counters are displayed or communicated with the time stamp (date & time) of the last reset. Measuring function: total active energy meter without reset function and partial active energy meter with reset function. Extended measurement function for energy meters via display and communication: active/reactive energy meter and current per phase, active power, total power factor, average voltage. Only via communication: voltage, active power per phase, frequency. Further order options: Billing metering: MID-compliant in accordance with EN 50470-3 (formerly PTB approval), total and per phase active energy meter. Degree of protection: Front IP 40, housing IP 20 (Note on MID variants: for conformity with the European Measuring Instruments Directive MID 2004/22/EG, the measuring device must be installed in a cabinet or housing with degree of protection IP51 or better).

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

