



Flush-mounted housing for ER EC - Ventilator housing for inlying bathrooms ER GH



Maico
ER GH
0084.0350
4012799843504 EAN/GTIN

5426,74 INR excl. VAT**
plus shipping



16-17 days* (IND)

Flush-mounted housing for ER EC ER GH Housing material Plastic, color black, connection diameter 75mm, installation height 250mm, installation width 250mm, installation depth 110mm, ER-A - standard version: standard cover with filter change indicator. Not speed controllable. The device runs in continuous operation at the base load level at 30 m3/h. On/off of the full load level via light switch or separate switch. Switching to full load level (60 m3/h) with switch-on delay of approx. 60 seconds. Follow-up time of the full load approx. 15 min. Circuit variant: The base load can be switched on or off with an additional switch (see circuit diagrams on the Internet). Contemporary design. Suitable for continuous operation. Protection class IP X5 for safety in the bathroom. Color traffic white similar to RAL 9016. For one-room ventilation with a single fan. With filter change indicator. Easy filter change without tools. Cover can be rotated by +/- 5°, allowing compensation if the housing is inserted at an angle. Protection class II. Energy-saving EC motor. Motor with thermal overload protection. Maintenance-free, with ball bearings closed on both sides. Article: ER-A, design: standard, delivery volume: 30 m3/h / 60 m3/h / (level 1/level 2), speed: 800 rpm / 1250 rpm, air direction : ventilation, SEC average: -13.1 kWh/(m2 a), type of voltage: alternating current, rated voltage: 230 V, mains frequency: 50 Hz, power consumption: 2.5 W / 5 W, protection class: IP X5, mains cable: 4 / 1.5 mm2 auort: wall / ceiling, system type: decentralized, housing material: plastic, colour: traffic white, similar to RAL 9016, weight: 0.6 kg, filter class: G2, width: 281 mm, height: 281 mm, depth: 33 mm, conveying medium temperature at IMax: 40 °C, sound pressure level: 15 dB(A) / 35 dB(A) / specification according to DIN 18017-3 with an equivalent absorption area AL = 10 m2

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

