



**LED recessed downlight 2700K dim.DALI -
Downlight/spot/floodlight 1x8W 901573.002.76**



RZB

901573.002.76

4051859218272 EAN/GTIN

9034,30 INR excl. VAT**

plus shipping



16-17 days* (IND)

LED built-in downlight 2700K dim.DALI 901573.002.76 Suitable for built-in installation, Suitable for ceiling installation, Adjustability not adjustable, Light source LED cannot be replaced, With light source, Suitable for number of light sources 1, Housing material aluminium, Surface powder-coated, Housing color white, Cover material plastic opal, type of voltage AC/DC, nominal voltage 220 ... 240V, control gear LED control gear, current-controlled, with control gear, dimming dependent on control gear, DALI dimming, reflector without, light distributor without, light distribution symmetrical, beam angle unshielded/diffuse, light emission direct, distortion factor (THD) 0.2, rated service life L70/B50 at 25 °C 50000h, degree of protection (IP) IP44, degree of protection (NEMA) other, impact resistance IK05, protection class II, rated ambient temperature according to IEC62722-2-1 25 ... 25°C, suitable for lamp power 8 ... 8W, max. system power 9W, light color white, color temperature 2700 ... 2700K, color rendering index CR I 80-89, luminous flux 760 ... 760lm, rated luminous flux according to IEC 62722-2-1 760lm, lamp luminous efficacy 95lm/W, power factor 0.95, height/depth 2mm, outer diameter 130mm, installation height/depth 140mm, installation diameter 105mm, Art of the wiring suitable for through-wiring, number of poles 5, conductor cross-section 2.5mm², connectable conductor cross-section 1.5 ... 1.5mm², connection type plug-in terminal, luminous efficiency of luminaire 85lm/W, glow-wire test according to IEC 60695-2-11 750 °C - 30 s, photobiological Safety according to EN 62471 RG0, color consistency (MacAdam ellipse) SDCM4, highly efficient recessed LED downlight in three sizes. Housing and opal plastic diffuser made of UV-resistant polycarbonate. Homogeneous and soft illumination. Protection class IP 44. Light output up to 117 lm/W. LED service life 50,000 h (L70, B50). Minimum color tolerances: 4x MacAdam (4 SDCM). Suitable for through wiring. Tool-free installation thanks to spring attachment. Light color 827. Color rendering Ra > 80. Cover ring: die-cast aluminium, powder-coated. Plastic housing (polycarbonate, UV-resistant). Diffuser plastic (polycarbonate, UV-resistant) opal, impact-resistant. With spring attachment. Passive cooling. Suitable for through wiring. Control gear external. Bulbs (LED) included.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

