

**LED emergency surface-mounted downlight 4000K 8h -
Emergency luminaire 20W IP40 8h 672276.002.1**



RZB

672276.002.1

4051859215608 EAN/GTIN

20295,37 INR excl. VAT**

plus shipping



16-17 days* (IND)

LED emergency surface-mounted downlight 4000K 8h 672276.002.1 Type of installation Ceiling surface-mounting, Escape route lighting function, Suitable for marking type other, Type of marking not applicable, Monitoring device automatic self-test, Switching type maintained/standby mode, Feed-in decentralized (individual battery), Battery quality NiMh, Light source LED not replaceable, With lamp, Suitable for number of lamps 1, socket without, number of lamp heads 1, housing material steel, housing color white, cover material plastic opal, type of voltage AC, nominal voltage 200 ... 200V, control gear LED control gear current-controlled, light distributor without, energy efficiency class of the permanently installed lamp A++, A+, A (LED), protection class (IP) IP40, protection class (NEMA) other, impact resistance IK06, protection class I, rated ambient temperature according to IEC62722-2-1 25 ... 25°C, max. system power 20W, rated luminous flux according to IEC 62722-2-1 1650lm, luminous flux in S tandby mode 180lm, color temperature 4000 ... 4000K, nominal operating time 8 ... 8h, width 225mm, height/depth 58mm, length 225mm, type of wiring termination, number of poles 4, conductor cross-section 2.5mm², connection type plug-in connection, design continuity with general lighting. We offer a comprehensive product range in the field of safety lighting and general lighting. In this way, we can offer our customers integrated solutions for all areas of application, depending on the construction project. LED service life 50,000 h (L70, B10). Light guide and plastic cover made of non-yellowing PMMA. Also suitable for large ceiling heights. Installation friendly. Large luminaire spacing for escape route lighting. Unobtrusive design. Attachment housing made of sheet steel, powder-coated. Square cover plate, die-cast aluminium, powder-coated. Light guide and plastic cover made of non-yellowing plastic (PMMA). Cover plastic opal matt. Built-in operating devices. Bulbs (LED) included. Single battery system with integrated self-test. Energy efficiency class A+ | A+

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

