

Item Number EB12207318

https://www.eibabo.in/rzb/wall-ceiling-light-e27-qa60-57w-ceiling-wall-luminaire-1x57w-582007.002-eb 12207318



Wall-ceiling light E27 QA60/57W - Ceiling-/wall luminaire 1x57W 582007.002

RZB

582007.002 4051859217633 EAN/GTIN



8277,42 INR excl. VAT**

plus shipping



16-17 days* (IND)

Wall/ceiling light E27 QA60/57W 582007.002 Suitable for wall mounting, Suitable for ceiling mounting, Suitable for surface mounting, Lamp HV halogen lamp, Suitable for VDU workstations according to EN 12464-1, Suitable for number of lamps 1, Socket E27, Housing material aluminium, Housing color white, Material of the Cover plastic opal, version of the louvre without, type of voltage AC/DC, operating device not required, dimming mains voltage modulation, without dimming function, light distributor without, light distribution symmetrical, beam angle extremely wide beam >80°, light emission direct, protection class (IP) IP66, protection class (NEMA) other, impact strength IK10, protection class I, rated ambient temperature according to IEC 662722-2-1 -20 ... -20°C, suitable for emergency light, glow wire test according to IEC 66695-2-11 850 °C - 30 s, suitable for lamp power 57 .. 57W, Max Cut 1.5mm², connection type plug-in terminal, elegant appearance without visible screws thanks to bayonet lock with snap lock. LED: Use of smart, low-cost LED modules for mains voltage with high LED system light output for energy-saving operation. Housing made of corrosion-resistant die-cast aluminium, powder-coated, robust design, stainless steel screws. Fast installation: Tolerance compensation for drill holes. Generous cable management space also allows wall outlets in the center of the luminaire. Electrical connection via plug-in terminals. Enormous range of variants: 24 possible versions per configuration, based on two variants: pressed glass with a satin finish or impact-resistant, opal plastic (PC). Three standard colors. Four housing variants: Flat cover or spherical cap, half-shell, protective basket. Fastening points outside the lamp compartment, safe installation through consistent avoidance of errors. Extended range of application up to +50° C ambient temperature. Second cable entry for network forwarding. Other equipment variants: As a house number light with an integrated twillight switch. Versions for escape routl

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

