

Item Number EB13322000

×

https://www.eibabo.in/rzb/led-wall-ceiling-emergency-light-4000k-emergency-luminaire-8-4w-ip66-6722 84.0031.89-eb13322000



LED wall/ceiling emergency light 4000K - Emergency luminaire 8,4W IP66 672284.0031.89

RZB

672284.0031.89 4051859217954 EAN/GTIN

19088,16 INR excl. VAT**

plus shipping

📕 🔰 16-17 days* (IND)

LED wall/ceiling emergency light 4000K 672284.0031.89 Type of mounting Wall mounting/ceiling mounting, Escape route lighting function, Suitable for marking type Other, Type of marking not applicable, Monitoring device Monitoring module (centrally supplied system), Switching type maintained/standby mode, Central feed (central battery), Battery properties Other, Light source LED not interchangeable, With light source, Suitable for number of light sources 1, Socket without, Number of light heads 1, Housing material aluminium, Housing color anthracite, Cover material plastic opal, Type of voltage AC/DC, Rated voltage 220 ... 240V, Control gear Current-controlled LED control gear, light distributor without, energy efficiency class of the permanently installed lamp A++, A (LED), degree of protection (IP) IP66, degree of protection (NEMA) other, impact resistance IK10, protection class I, luminaire with limited surface temperature 'D mark'', Rated ambient temperature according to IEC6 2722-2-1 25 ... 25°C, max. system power 8.4W, rated luminous flux according to IEC 62722-2-1 530Im, luminous flux in standby mode 520Im, color temperature 4000 ... 4000K, power factor 0.54, height /depth 91mm, outer diameter 268mm, type of wiring termination, number of poles 5, conductor cross-section 2.5mm², connection type plug-in connection, elegant appearance without visible screws thanks to bayonet catch with snap lock. LED: Use of smart, low-cost LED modules for mains voltage with high LED system light output for energy-saving operation. Housing made of corrosion-resistant die-cast aluminium, powder-coated, robust design, stainless steel screws. Fast installation: Tolerance compensation for drill holes. Generous cable management space also allows wall outlets in the center of the luminaire. Electrical connection via plug-in terminals. Fastening points outside the lamp compartment, safe installation through consistent avoidance of errors. Seawater resistant coating opticnally available. Fitting and housing made of corrosion-resistan

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

