
×



Item Number EB12207285

https://www.eibabo.in/rzb/led-wall-ceiling-light-3000k-w.bwm-ceiling-wall-luminaire-1x13w-581637.004. 19-eb12207285



LED wall-ceiling light 3000K w.BWM - Ceiling-/wall luminaire 1x13W 581637.004.19

RZB

581637.004.19 4051859224990 EAN/GTIN

19026,94 INR excl. VAT**

plus **shipping**



16-17 days* (IND)

LED wall ceiling light 3000K with BWM 581637.004.19 Energy efficiency class of the supplied replaceable light source A+, Highest energy efficiency class of the replaceable light source A+, Lowest energy efficiency class of the replaceable light source A+, Energy efficiency class spectrum A++ to E, Suitable for wall mounting, Suitable for ceiling mounting, Suitable for Surface mounting, Light source LED not interchangeable, With light source, Suitable for number of light sources 1, Other socket, Housing material aluminium, Housing color silver, Cover material glass opal, Design of the grid without, Type of voltage AC, Nominal voltage 220 ... 240V, Control gear LED Current-controlled control gear, with control gear, without dimming function, light distributor without, symmetrical light distribution, beam angle unshielded/diffuse, light emission direct, rated service life L70/B50 at 25 °C 50000h, protection class (IP) IP65, protection class (NEMA) other, impact resistance IK05, protection class I, design ing ambient temperature according to IEC62722-2-1 -20 ... 41°C, with motion detector, with light sensor, glow wire test according to IEC 60695-2-11 960 °C - 30 s, suitable for lamp power 13 ... 13W, max. system power 13W, Rated luminous flux according to IEC 62722-2-1 630lm, light color white, color temperature 3000 ... 3000K, color rendering index CRI 80-89, luminous efficacy of luminaire 49lm/W, width 257mm, height/depth 81mm, length 257mm, type of wiring termination, number of positions 3, Conductor cross-section 2.5mm², Connection type plug-in terminal, The flat design offers universal applicability with either a round or square glass cover. The cover, made of crystal glass with a frosted interior, also shines during the day. Use of smart, cost-effective LED modules for mains voltage with high LED system light output for energy-saving operation. Longevity thanks to the use of high-quality materials such as aluminium, crystal glass and stainless steel as well as durable powder coating. Coordination of the appearance of the environment with the surrounding lighting by selecting the light color 830 or 840. The high degree of protection IP 65 allows maintenance-free, trouble-free LED operation. Also available in a safety lighting version. Housing made of corrosion-resistant die-cast aluminum for outdoor use, powder-coated. Cover with crystal glass, frosted on the inside. Screwless installation of the cover with snap lock. Fastening outside of the sealed area with bore tolerance compensation. Light source (mains voltage LED module) included. Standard with diaphragm valve to prevent condensation. With...

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500.000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

