×



## Item Number EB12207152

https://www.eibabo.in/rzb/led-wall-ceiling-light-2700-6500k-ceiling-wall-luminaire-1x33w-312269.004.2. 730-eb12207152



LED wall ceiling light 2700-6500K - Ceiling-/wall luminaire 1x33W 312269.004.2.730

## **RZB**

312269.004.2.730 4051859269540 EAN/GTIN

## **54633,49 INR** excl. VAT\*\*

plus shipping bulky item



16-17 days\* (IND)

LED wall-ceiling light 2700-6500K 312269.004.2.730 Suitable for wall mounting, Suitable for ceiling mounting, Suitable for surface mounting, LED bulbs cannot be replaced, With bulbs, Suitable for computer workstations according to EN 12464-1, Suitable for number of bulbs 1, Other socket, Housing material aluminium, Housing color aluminium, Cover material structured plastic, Design of the louvre without, Voltage type AC, Nominal voltage 220 ... 240V, Control gear LED control gear, current-controlled, With control gear, Manufacturer-specific dimming, Dimming dependent on the control gear, Light distributor without, Light distribution symmetrical, Beam angle unshielded /diffuse, light emission direct, rated service life L70/B10 at 25 °C 50000h, degree of protection (IP) IP40, degree of protection (NEMA) other, impact resistance IK03, protection class I, rated ambient temperature according to IEC62722-2-1 25 ... 25°C, glow wire test according to IEC 60695-2-11 650 °C - 30 s, suitable for lamp power 33 ... 33 W, max. system power 28W, rated luminous flux according to IEC 62722-2-1 3350lm, light color multicolored, color temperature 2700 ... 6500K, color rendering index CRI 80-89, luminous efficacy of luminaire 120lm/W, power factor 0.98, width 298mm, height/depth 49mm, length 1198mm, type of wiring termination, number of poles 3, conductor cross-section 1.5mm², connection type plug-in terminal, highly aesthetic series of lights with extremely flat overall height and progressive LED technology. RZBSIDELITE® technology: Lateral light coupling for above-average homogeneous luminance distribution. LED service life 50,000 h (L70, B10). Glare rating UGR: 19.0. Light guide and plastic cover made of non-yellowing PMMA. Infinitely height-adjustable 2-point steel wire suspension. Very simple installation thanks to Plug & Play connection system.

## YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



**COMPLAINTS HANDLING**Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION





25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

