

**LED lay-in lamp 2700-6500K - Ceiling-/wall luminaire
1x32W 312273.002.2.730****RZB**

312273.002.2.730

4051859269694 EAN/GTIN

24432,66 INR excl. VAT**

plus shipping bulky item



16-17 days* (IND)

LED lay-in luminaire 2700-6500K 312273.002.2.730 Suitable for ceiling mounting, Suitable for recessed mounting, LED illuminant cannot be replaced, With illuminant, Suitable for computer workstations according to EN 12464-1, Suitable for number of illuminants 1, Other socket, Housing material aluminium, Housing color white, Material of the Structured plastic cover, louvre design without, Voltage type AC, Rated voltage 220 ... 240V, Control gear LED control gear, current-controlled, With control gear, Manufacturer-specific dimming, Dimming dependent on control gear, Other light distributor, Symmetrical light distribution, Beam angle unshielded/diffuse, Direct light emission, Rated service life L70/B10 at 25 °C 50000h, degree of protection (IP) IP40, degree of protection (NEMA) other, impact resistance IK03, protection class II, rated ambient temperature according to IEC62722-2-1 25 ... 25°C, glow wire test according to IEC 60695-2- 11 650 °C - 30 s, Suitable for lamp power 32 ... 32W, Max. system power 32W, B Measurement luminous flux according to IEC 62722-2-1 3000lm, light color multicolored, color temperature 2700 ... 6500K, color rendering index CRI 80-89, luminous efficacy of luminaire 94lm/W, power factor 0.97, width 595mm, length 595mm, installation height/depth 160mm, type of Wiring termination, 2 poles, conductor cross-section 2.5mm², connection type screw terminal, highly economical series of lights with progressive LED technology, consisting of ceiling, wall, inset installation and pendant lights for indoor use. Suitable for use in the food and beverage industry. Light guide and plastic cover made of non-yellowing PMMA with fine microprismatics. RZB SIDELITE® technology: Lateral light coupling for above-average homogeneous luminance distribution. LED service life 50,000 h (L70, B10). Up to 109 lm per watt. Flicker < 5%. Extremely flat overall height (10 mm). Extremely simple converter installation thanks to the rotary plug-in system and extended converter connection cable to the light. Versions with smart+free Bluetooth control for wireless networking and operation using an Android / iOS device, free app available for download.

YOUR ADVANTAGES**WORLDWIDE TRADE**

Corporate video eibmarkt®

**COMPLAINTS HANDLING**

Obliging and 100% safely

**SHORT DELIVERY TIME**

Warehousing

**99% CUSTOMER SATISFACTION**

> 500,000 customers worldwide

**25 YEARS OF EXPERIENCE**

In worldwide mail order

**REFUND**

Within 14 days

**DHL TRACK & TRACE**

Shipment tracking

**ORDER LIVE CHAT**

With order history

**DATA PROTECTION**

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

