


Item Number EB12207303

https://www.eibabo.in/rzb/led-wall-ceiling-light-3000k-w.bwm-ceiling-wall-luminaire-1x21w-581641.004. 19-eb12207303



LED wall-ceiling light 3000K w.BWM - Ceiling-/wall luminaire 1x21W 581641.004.19

×

RZB

581641.004.19 4051859227519 EAN/GTIN

24504,68 INR excl. VAT**

plus shipping



16-17 days* (IND)

LED wall-ceiling light 3000K m.BWM 581641.004.19 Suitable for wall mounting, Suitable for ceiling mounting, Suitable for surface mounting, Light source LED not interchangeable, With light source, Suitable for number of light sources 1, Other socket, Housing material aluminium, Housing color silver, Material of the Cover glass opal, version of the louvre without, type of voltage AC, nominal voltage 220 ... 240V, control gear LED control gear, current-controlled, with control gear, without dimming function, light distributor without, light distributor symmetrical, beam angle unshielded/diffuse, light emission direct, protection class (IP) IP65, Degree of protection (NEMA) other, Impact resistance IK07, Protection class I, Rated ambient temperature according to IEC62722-2-1 -20 ... 40°C, With motion detector, Glow wire test according to IEC 6695-2-11 960 °C - 30 s, Suitable for lamp power 21 ... 21W, max. system power 22W, rated luminous flux according to IEC 62722-2-1 1150Im, light color white, color temperature 3000 ... 3000K, color rendering in dex CRI 80-89, luminous efficacy of luminaire 53Im/W, height/depth 127mm, outer diameter 400mm, type of wiring termination, number of poles 3, conductor cross-section 1.5mm², connection type plug-in terminal, elegant appearance without visible screws thanks to bayonet catch with snap lock. The appropriate size also allows it to be used in generously designed outdoor areas without appearing lost. Fast installation: Tolerance compensation for drill holes. Generous cable management space also allows wall outlets in the center of the luminaire. Electrical connection via plug-in terminals. Fastening points outside the lamp compartment, safe installation through consistent avoidance of errors. Second cable entry for network forwarding. Can also be fitted with lamps for E27 sockets. Versions for escape route lighting with central battery feed available. Housing made of corrosion-resistant die-cast aluminum for outdoor use, powder-coated. Protective grille with diffuser spherica

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION





25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION *Guarantee*

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

