

**Wall-ceiling light E27 QA60/2x57W 581640.002****RZB**

581640.002

4051859227373 EAN/GTIN

**13537,51 INR** excl. VAT\*\*

plus shipping



16-17 days\* (IND)

Wall/ceiling light E27 QA60/2x57W 581640.002 Suitable for wall mounting, Suitable for ceiling mounting, Suitable for surface mounting, Light source HV halogen lamp, Suitable for VDU workstations according to EN 12464-1, Suitable for number of light sources 2, Socket E27, Housing material aluminium, Housing color white, Material of the Opal glass cover, design of the louvre without, type of voltage AC/DC, operating device not required, dimming mains voltage modulation, without dimming function, light distributor without, light distribution symmetrical, beam angle unshielded/diffuse, light emission direct, protection class (IP) IP65, protection class (NEMA) other, Impact resistance IK07, protection class I, rated ambient temperature according to IEC62722-2-1 -20 ... -20°C, suitable for emergency lighting, glow wire test according to IEC 60695-2-11 960 °C - 30 s, suitable for lamp power 57 ... 57W , power factor 1, height/depth 127mm, outer diameter 400mm, type of wiring termination, number of poles 3, conductor cross-section 1.5mm², connection type Stec klemme, Elegant appearance without visible screws thanks to the bayonet lock with snap lock. The appropriate size also allows it to be used in generously designed outdoor areas without appearing lost. Fast installation: Tolerance compensation for drill holes. Generous cable management space also allows wall outlets in the center of the luminaire. Electrical connection via plug-in terminals. Fastening points outside the lamp compartment, safe installation through consistent avoidance of errors. Second cable entry for network forwarding. Can also be fitted with lamps for E27 sockets. Versions for escape route lighting with central battery feed available. Housing made of corrosion-resistant die-cast aluminum for outdoor use, powder-coated. Protective grille with diffuser spherical cap made of opal glass with mounting fixation. Screwless installation of the diffuser via bayonet catch with snap lock. Fastening outside the sealed area with bore tolerance compensation. Mains connection 2x 3x 1.5 mm². Energy efficiency class A, C, EI A+

**YOUR ADVANTAGES****WORLDWIDE TRADE**

Corporate video eibmarkt®

**99% CUSTOMER SATISFACTION**

&gt; 500,000 customers worldwide

**DHL TRACK & TRACE**

Shipment tracking

**COMPLAINTS HANDLING**

Obliging and 100% safely

**25 YEARS OF EXPERIENCE**

In worldwide mail order

**ORDER LIVE CHAT**

With order history

**SHORT DELIVERY TIME**

Warehousing

**REFUND**

Within 14 days

**DATA PROTECTION**

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

**eibabo®** and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

**eibabo®** the Smart Home technology shop  
**eibabo®** electronics cheap online order  
**eibabo®** electric appliances buy online

