



**LED wall light 4000K insulation. - Ceiling-/wall luminaire
1x4W 582004.002.25**



RZB
582004.002.25
4051859217541 EAN/GTIN

13093,45 INR excl. VAT**
plus shipping

 **16-17 days* (IND)**

LED wall light 4000K insulation. 582004.002.25 Suitable for wall mounting, Suitable for surface mounting, LED illuminant cannot be replaced, With illuminant, Suitable for computer workstations according to EN 12464-1, Suitable for number of illuminants 1, Other socket, Housing material aluminium, Housing color white, Cover material opal glass, Version of the Louvre without, Type of voltage AC, Rated voltage 220 ... 240V, Control gear not required, Without dimming function, Light distributor without, Light distribution symmetrical, Beam angle unshielded/diffuse, Light emission direct, Rated service life L70/B50 at 25 °C 35000h, Degree of protection (IP) IP66, Degree of protection (NEMA) other, impact resistance IK08, protection class I, rated ambient temperature according to IEC62722-2-1 -20 ... 60°C, glow wire test according to IEC 60695-2-11 960 °C - 30 s, suitable for lamp power 4 ... 4W, max. system power 4W, rated luminous flux according to IEC 62722-2-1 160lm, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, luminous exchange yield 40lm/W, height/depth 70mm, outer diameter 268mm, type of wiring termination, number of poles 3, conductor cross-section 2.5mm², connection type plug-in terminal, elegant appearance without visible screws thanks to bayonet catch with snap lock. LED: Use of smart, low-cost LED modules for mains voltage with high LED system light output for energy-saving operation. Housing made of corrosion-resistant die-cast aluminium, powder-coated, robust design. Fast installation: Tolerance compensation for drill holes. Generous cable management space also allows wall outlets in the center of the luminaire. Electrical connection via plug-in terminals. Fastening points outside the lamp compartment, safe installation through consistent avoidance of errors. Second cable entry for network forwarding. Seawater resistant coating optionally available. Housing made of corrosion-resistant die-cast aluminum for outdoor use, powder-coated. Planar diffuser in opal glass with mounting fixation. Screwless installation of the diffuser via bayonet catch with snap lock. Fastening outside the sealed area with bore tolerance compensation. Light source (mains voltage LED module) included. Including built-in twilight switch. Mains connection 2x 3x 1.5 mm².

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler at a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

