

**LED wall-ceiling light 4000K HF-BWM - Ceiling-/wall luminaire 1x10W 582003.0031.19****RZB**

582003.0031.19

4051859217435 EAN/GTIN

15687,33 INR excl. VAT**

plus shipping



16-17 days* (IND)

LED wall-ceiling light 4000K HF-BWM 582003.0031.19 Suitable for wall mounting, Suitable for ceiling mounting, Suitable for surface mounting, LED bulbs cannot be replaced, With bulbs, Suitable for computer workstations according to EN 12464-1, Suitable for number of bulbs 1, Other socket, Housing material aluminium, housing color anthracite, cover material opal plastic, design of the louvre without, type of voltage AC, nominal voltage 220 ... 240V, control gear not required, without dimming function, light distributor without, light distribution symmetrical, beam angle unshielded/diffuse, light emission direct, rated service life L70/ B50 at 25 °C 45000h, degree of protection (IP) IP66, degree of protection (NEMA) other, impact resistance IK10, protection class I, rated ambient temperature according to IEC62722-2-1 -20 ... 41°C, with motion detector, glow wire test according to IEC 60695-2 -11 850 °C - 30 s, suitable for lamp power 10 ... 10W, max. system power 10W, rated luminous flux according to IEC 62722-2- 1 360lm, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, luminous efficacy of luminaire 36lm/W, height/depth 91mm, outer diameter 268mm, type of wiring termination, number of poles 3, conductor cross-section 2.5mm², connection type plug-in terminal, elegant appearance without visible screws thanks to bayonet lock with snap lock. LED: Use of smart, cost-effective LED modules for mains voltage with high LED system light output for energy-saving operation. Housing made of corrosion-resistant die-cast aluminium, powder-coated, robust design, stainless steel screws. Fast installation: Tolerance compensation for drill holes. Generous cable management space also allows wall outlets in the center of the luminaire. Electrical connection via plug-in terminals. Enormous range of variants: 24 possible versions per configuration, based on two variants: pressed glass with a satin finish or impact-resistant, opal plastic (PC). Three standard colors. Four housing variants: Flat cover or spherical cap, half-shell, protective basket. Fastening points outside the lamp compartment, safe installation through consistent avoidance of errors. Extended range of application up to +50° C ambient temperature. Second cable entry for network forwarding. Other equipment variants: As a house number light with an integrated twilight switch. Versions for escape route lighting with central battery feed. Housing made of corrosion-resistant die-cast aluminum for outdoor use, powder-coated. Diffuser spherical cap made of opal plastic (polycarbonate) with mounting fixture. Screwless installation of the diffuser...

YOUR ADVANTAGES**WORLDWIDE TRADE**

Corporate video eibmarkt®

**COMPLAINTS HANDLING**

Obliging and 100% safely

**SHORT DELIVERY TIME**

Warehousing

**99% CUSTOMER SATISFACTION**

> 500,000 customers worldwide

**25 YEARS OF EXPERIENCE**

In worldwide mail order

**REFUND**

Within 14 days

**DHL TRACK & TRACE**

Shipment tracking

**ORDER LIVE CHAT**

With order history

**DATA PROTECTION**

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

