

# Item Number EB16408260

https://www.eibabo.in/steinel/presence-detector-10m-ir-qu-hd-daliplus-de-eb16408260



#### Presence detector 10m IR QU HD DALIPLUS DE



#### Steinel

IR QU HD DALIPLUS DE 035204 4007841035204 EAN/GTIN

## 16853,62 INR excl. VAT\*\*

plus **shipping** 



16-17 days\* (IND)

Presence detector IR QU HD DALIPLUS DE Presence detector version, sensor type passive infrared, with DALI interface, constant light control, forced shutdown, creep under protection/rear field monitoring, networkable, optimal installation height 2.8m, bypass switch, max. range to one side 10m, max. presence area 8m², max Frontal range 10m, detection field diameter on the floor 8m, remote controllable, response brightness adjustable, with signal unit, teach function for response brightness, suitable for ceiling mounting, dimming function with dimming insert, mounting type other, connection type other, material plastic, material quality thermoplastic, halogen-free, surface other, Design of the surface matt, color white, RAL number (similar) 9010, protection class (IP) IP20, type of voltage AC, frequency 50 ... 60Hz, nominal voltage 240V, min. switch-on time 5s, max. switch-on time 60min, switch-off delay 300s, horizontal detection angle 360 ... 360°, response brightness 10 ... 1000lx, max 2000W, suitable for C-load, temperature 0 ... 40°C, number of switching zones 4800, max. inrush current 10.4 min. inrush current 0.1A, control current 150mA, extension input, alarm function, width 120mm, height 124mm, depth 124mm, installation width 120mm, installation depth 124mm, installation length 120mm, entry into intelligent lighting control. Intelligent infrared presence detector IR Quattro HD DALI plus with extensive additional functions, ideal for classrooms, open-plan offices and car parks, installation height up to 10 m, with three light channels (DALI addressable) for up to 64 lights, easy to set up via app. Additional potential-free relay, constant light control and variable basic lighting functions, button interface for all 3 light channels for pressing and dimming as well as for the potential-free relay (light operation), remotely controllable via Smart Remote.

### YOUR ADVANTAGES



**WORLDWIDE TRADE**Corporate video eibmarkt®



COMPLAINTS HANDLING
Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



**25 YEARS OF EXPERIENCE** *In worldwide mail order* 



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- \*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- \*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

