

Item Number EB12806500

27.04.2024/01:27

https://www.eibabo.in/brumberg/led-recessed-spotlight-d2w-3000k-nickel-dimm.-downlight-spot-floodlig ht-1x6w-39374153-eb12806500

LED recessed spotlight d2w 3000K nickel dimm. -Downlight/spot/floodlight 1x6W 39374153

Brumberg 39374153 4251433917359 EAN/GTIN

5034,74 INR excl. VAT**

plus **shipping**

馬 16-17 days* (IND)

LED recessed spotlight d2w 3000K nickel dimm. 39374153 Energy efficiency class of the built-in light source A++, A+, A (LED), Suitable for recessed mounting, Suitable for ceiling mounting, Pivotable adjustability, LED light source cannot be replaced, With light source, Suitable for number of light sources 1, Socket without, Housing material other, Housing color nickel, Type of voltage AC, nominal voltage 230... 230V, control gear LED control gear current-controlled, with control gear, trailing edge dimming, highly specular reflector, light distribution symmetrical, beam angle medium beam 21-40°, light emission direct, protection class (IP) IP20, protection class II, suitable for lamp power 6... 6W, max. system power 6W, light color white, color temperature 1800... 3000K, color rendering index CRI 80-89, luminous flux 460... 460Im, rated luminous flux according to IEC 62722-2-1 460Im, width 82mm, length 82mm, Installation height/depth 50mm, installation diameter 68mm, LED recessed spotlight set BB14, dim2warm, dimmable, nickel. Designed in a compact design for tool-free quick assembly for ceiling installation. If the luminaire is dimmed, the color temperature decreases. Set incl. converter 7230 V mains voltage, trailing edge, converter dimensions: L 110 x W 50 x H 19 mm. Socket: without, mounting type: recessed mounting, mounting location: ceiling mounting, material: cast iron / aluminum / glass, protection class: according to DIN EN 60529: IP20, protection class: (EN 61140) II, voltage: 230V AC 50Hz, power: 6W, number of lamps / Sockets: 1.0 pieces, luminous flux: 460Im, color temperature: 3000 to 1800K, beam angle: 38°, adjustability: pivotable, with control gear, type of dimming: trailing edge

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online





×