



Frame 1x R.1 copper/pws MAN0106017



Berker
MAN0106017
4011334541332 EAN/GTIN

8077,18 INR excl. VAT**
plus shipping



16-17 days* (IND)

Frame 1x R.1 copper/pws MAN0106017 Number of units 1, mounting direction horizontal and vertical, number of units horizontally 1, number of units vertically 1, number of modules horizontally (with modular design) 0, number of modules vertically (with modular design) 0, number of switch inserts 1, suitable for flush-mounted installation, suitable for device installation trunking, suitable for built-in installation, material metal, material quality copper, halogen-free, surface brushed, surface design matt, color copper, degree of protection (IP) IP20, type of fastening clamp fastening, width 81.2mm, height 81.2mm, depth 9.9mm, hole diameter (opening) 52mm, frame 1x R.1 copper/polar white. R.1 Program description Long text Switch program made of thermoplastic, unbreakable and impact-resistant, in the colors polar white (RAL 9010), black (RAL 9005), frame 1-way to 5-way, can be used vertically and horizontally. The socket center pieces and many other center pieces form an edgeless surface with the frame. Square basic shape and round corners 12 mm radius. With flat geometry and glossy surface. Round rockers/covers with a diameter of 58mm. Alternatively: switch range made from a 7 mm high thermoplastic carrier with a 3 mm glass surface on it, scratch-resistant, in the colors polar white (RAL 9010), black (RAL 9005), frame 1x to 5x, vertical like can be used horizontally. The socket center pieces and many other center pieces form an edgeless surface with the frame. Square basic shape and round corners 12 mm radius. With flat geometry and glossy surface. Round rockers/covers with a diameter of 58 mm. Installation devices can be used in some cases with a separate sealing set that is water-protected UP IP 44. Possibility of labeling with frames that can be labeled, abrasion-resistant labeling of the products with printing. Can be illuminated according to workplace regulations. The material used is halogen-free and UV-stable, the surfaces are easy to clean and are resistant to disinfectants. Over 150 applications.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

