

×

https://www.eibabo.in/berker/frame-5x-r.1-copper-pws-man0106417-eb10869878

## Frame 5x R.1 copper/pws MAN0106417

Berker

MAN0106417 4011334541370 EAN/GTIN

47692,62 INR excl. VAT\*\*

plus shipping

lind 16-17 days\* (IND)

Frame 5x R.1 copper/pws MAN0106417 number of units 5, mounting direction horizontal and vertical, number of units horizontally 5, number of units vertically 5, number of modules horizontally (in modular design) 0, number of switch inserts 5, suitable for flush-mounted installation, suitable for device installation trunking, suitable for built-in installation, material metal, material quality copper, halogen-free, surface brushed, surface design matt, color copper, protection class (IP) IP20, type of fastening clamp fastening, width 365.2 mm, height 81.2 mm, depth 9.9 mm, hole diameter (opening) 52 mm, frame 5x R.1 copper/polar white. R.1 Program description Long text Switch program made of thermoplastic, shatterproof and impact-resistant, in the colors polar white (RAL 9010), black (RAL 9005), frame 1x to 5x, can be used vertically and horizontally. The socket center pieces and many other center pieces form an edgeless surface with the frame. Square basic shape and round corners 12 mm radius. With flat geometry and glossy surface. Round rockers/covers with a diameter of 58mm. Alternatively: switch range made form a 7 mm high thermoplastic carrier with a 3 mm glass surface on it, scratch-resistant, in the colors polar white (RAL 9010), black (RAL 9005), frame 1x to 5x, vertical like can be used horizontally. The socket center pieces form an edgeless surface with the frame. Square basic shape and round glossy surface. Round rockers/covers with a diameter of 58 mm. Alternatively: range of switches made from a 7 mm high thermoplastic carrier with a 3 mm metal surface on it made of stainless steel or aluminium, impact-resistant and unbreakable, frame 1-way to 5-way, can be used vertically and horizontally. The socket center pieces and many other center pieces form an edgeless surface with the frame. Square basic shape and round corners 12 mm radius. With flat geometry and glossy surface on it made of 58 mm. Installation devices can be used in some cases with a separate sealing set that is water-protected UP IP 44. P

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL). \*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries

outside the EU. \*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

