


Item Number EB12907022

https://www.eibabo.in/ledvance/led-recessed-spotlight-3000k-sw-downlight-spot-floodlight-spot-squark adi8w3kwt-eb12907022



LED recessed spotlight 3000K sw - Downlight/spot/floodlight SPOT SQUARKADJ8W3KWT

WT ×

LEDVANCE

SPOT SQUARKADJ8W3KWT 4058075114043 4058075114043 EAN/GTIN

3873,59 INR excl. VAT**

plus shipping



16-17 days* (IND)

LED recessed spotlight 3000K sw SPOT SQUARKADJ8W3KWT Energy efficiency class of the built-in light source A++, A+, A (LED), Suitable for recessed mounting, Suitable for ceiling mounting, Adjustability swivelling, LED light source cannot be replaced, With light source, Housing material aluminium, Powder-coated surface, Housing color white, Cover material Structured plastic, Type of voltage AC, Rated voltage 220 ... 240V, LED rated current at constant current 65 ... 65mA, Control gear LED control gear, current-controlled, With control gear, Without dimming function, Reflector without, Focus lens light distributor, Light distribution symmetrical, Beam angle Medium beam 21-40°, light emission direct, distortion factor (THD) 19, rated service life L70/B10 at 25 °C 50000h, rated service life L70/B50 at 25 °C 50000h, rated service life L80/B10 at 25 °C 45000h, rated service life L80/B50 at 25 °C 45000h, rated service life L90/B50 at 25 °C 30000h, degree of protection (IP) IP20, impact resistance IK03, protection class II, rated ambient temperature according to IEC62722-2-1 -10 ... 40°C, max. system power 8W, light color white, color temperature 3000 ... 3000K, color rendering index CRI 80-89, luminous flux 650 ... 650lm, rated luminous flux according to IEC 62722-2-1 650lm, lamp luminous efficacy 90lm/W, power factor 0.5, width 83mm, height/depth 72mm, length 90mm, installation width 83mm, installation height/depth 90mm, installation length 83mm, type of wiring termination, number of poles 2, connection type other, luminous efficacy of luminaire 90lm/W, glow wire test according to IEC 60695-2-11 650 °C - 30 s, photobiological safety according to EN 62471 RG0, color consistency (McAdam ellipse) SDCM4, Recessed spotlight, adjustable, square. Product features: Adjustable tilt angle: +/- 20°. Initial Color Consistency: = 4 SDCM (Threshold Unit). Lens material: PMMA. Product advantages: cut-off angle for comfortable interior lighting. High light output. Die-cast aluminum housing for improved heat dissipation. Energy saving

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500.000 customers worldwide



25 YEARS OF EXPERIENCE
In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries

outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

