

Item Number EB12906818

https://www.eibabo.in/ledvance/led-light-bar-with-switch-4000k-strip-light-led-not-exchangeable-Incomp switch3004w-4k-eb12906818

LED light bar with switch 4000K - Strip Light LED not exchangeable LNCOMPSWITCH3004W 4K





LNCOMPSWITCH3004W 4K 4058075106093 4058075106093 EAN/GTIN



plus **shipping**



5-6 days* (IND)



LED light bar with switch 4000K LNCOMPSWITCH3004W 4K illuminant LED not interchangeable, with illuminant, material plastic, housing color white, type of voltage AC, nominal voltage 220 ... 240V, control gear electronic ballast, with control gear, without dimming function, light distributor diffuser lens/optics/panel , Rated service life L70/B10 at 25 °C 50000h, Rated service life L90/B50 at 25 °C 50000h, Rated service life L90/B50 at 25 °C 50000h, Rated service life L90/B50 at 25 °C 30000h, degree of protection (IP) IP20, protection class II, Luminaire can be covered with thermal insulation material, Glow wire test according to IEC 60695-2-11 650 °C - 30 s, With switch, Suitable for lamp power 4 ... 4W, max. system power 4W, rated luminous flux according to IEC 62722-2-1 450lm, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, power factor 0.5, width 28mm, height/depth 3f3mm, kind of Wiring with through-wiring, number of poles 2, connection type other, electrical connection with plug-in system, compact light with switch for individual or light line applications. Product Features: Built-in switch. Up to 10 lights can be connected to each other. Transparent end caps. Versions with luminous flux 400...1500 Im available. 4 different lengths available. High luminous efficacy: up to 110 Im/W. Glow wire test according to IEC 60695-2-12: 850 °C. Product advantages: Compact dimensions. Requires little space thanks to its compact dimensions. Seamless connectivity with up to 10 lights per continuous line installation. Practical switch installed directly on the light. Low-flicker light thanks to a special electronic ballast. Flexible installation in 2 different angles thanks to 2 mounting options. Flexible application thanks to a wide range of available lengths from 300 to 1200 mm. Angular connection possible with the enclosed cable. Areas of application: Direct replacement for luminaires with fluorescent lamps. Indoor applications. Corridors, entrance areas, stainwells, living rooms, ba

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

