



## Sensor exterior light - Ceiling-/wall luminaire L 331 LED ANT



**Steinel**  
L 331 LED ANT  
053093  
4007841053093 EAN/GTIN

**11390,44 INR** excl. VAT\*\*  
plus shipping



5-6 days\* (IND)

Ceiling-/wall luminaire, Suitable for wall mounting yes, Suitable for pendulum suspension no, Suitable for ceiling mounting no, Suitable for recessed mounting no, Suitable for surface mounting yes, Illuminant LED not interchangeable, With illuminants yes, Suitable for light band configuration no, Lamp holder other, Material of the housing Plastic, Housing color anthracite, Material of the cover Plastic opal, Type of grid without, Voltage AC, Rated voltage 220..240 V, LED rated current at constant current 220 mA, Operating device LED operating device current-controlled, With operating device yes, Dimming 0-10 V no, Dimming 1-10 V no, Dimming DALI no, Dimming DMX no, Dimming DSI no, Dimming Potentiometer (device-integrated) no, GPRS dimming no, Dimming LineSwitch no, Dimming manufacturer-specific no, Dimming Mains voltage modulation no, Dimming Phase section no, Dimming Phase control no, Programmable dimming yes, Dimming RF no, Dimming Sine Wave Reduction no, Dimming Touch and Dim no, Dimming Zigbee no, Dimming with push-button no, Without dimming function no, light distributor without, Light distribution symmetrical, Beam angle extremely wide beam > 80 °, Light outlet directly, Degree of protection (IP) IP44, Impact resistance IK10, Protection class II, Suitable for emergency light no, With motion detector yes, With light sensor yes, With louvers no, Suitable for lamp power 9 W, Max. System performance 9 W, Rated luminous flux according to IEC 62722-2-1 753 lm, Light color white, Color temperature 3000K, Color rendering index CRI 80-89, luminous efficacy 83.6667 lm/W, Power factor 0,85, Width 253 mm, Height/depth 270 mm, Length 124 mm, Number of poles 2, Conductor cross-section 2.5 mm², Connection type other

### YOUR ADVANTAGES



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

