×



Item Number EB13253305

https://www.eibabo.in/steinel/sensor-exterior-light-ceiling-wall-luminaire-l-691-led-pmma-antv2-eb1325 3305



Sensor exterior light - Ceiling-/wall luminaire L 691 LED PMMA ANTV2

Steinel

L 691 LED PMMA ANTV2 053031 4007841053031 EAN/GTIN

18933,26 INR excl. VAT**

plus shipping



16-17 days* (IND)

Ceiling-/wall luminaire, Suitable for wall mounting yes, Suitable for pendulum suspension no, Suitable for ceiling mounting no, Suitable for recessed mounting no, Suitable for surface mounting yes, Illuminant LED not interchangeable, With illuminants yes, Suitable for light band configuration no, Lamp holder other, Material of the housing Aluminum, Housing color anthracite, Material of the cover Plastic opal, Type of grid without, Voltage AC, Rated voltage 220..240 V, LED rated current at constant current 220 mA, Operating device LED operating device current-controlled, With operating device yes, Dimming 0-10 V no, Dimming 1-10 V no, Dimming DALI no, Dimming DMX no, Dimming DSI no, Dimming Potentiometer (device-integrated) no, GPRS dimming no, Dimming LineSwitch no, Dimming manufacturer-specific no, Dimming Mains voltage modulation no, Dimming Phase section no, Dimming Phase control no, Programmable dimming yes, Dimming RF no, Dimming Sine Wave Reduction no, Dimming Touch and Dim no, Dimming Zigbee no, Dimming with push-button no, Without dimming function no, light distributor without, Light distribution symmetrical, Beam angle extremely wide beam > 80 °, Light outlet directly, Degree of protection (IP) IP44, Impact resistance IK07, Protection class II, Suitable for emergency light no, With motion detector yes, With light sensor yes, With louvers no, Suitable for lamp power 9 W, Max. System performance 9 W, Rated luminous flux according to IEC 62722-2-1 753 Im, Light color white, Color temperature 3000K, Color rendering index CRI 80-89, luminous efficacy 83.6667 Im/W, Power factor 0,85, Width 291 mm, Height/depth 306 mm, Length 126 mm, Number of poles 2, Conductor cross-section 2.5 mm², Connection type other

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE



In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

