

LED lamp L-TUBE-B 4000K 550mm Gen. F - LED-lamp/Multi-LED B22d white L-TUBE-B #0206681GF



Ridi-Leuchten
L-TUBE-B #0206681GF
0206681GF
4029299481303 EAN/GTIN



4411,45 INR excl. VAT**
plus shipping



16-17 days* (IND)

LED lamp L-TUBE-B 4000K 550mm Gen. F L-TUBE-B 0206681GF Energy efficiency class A++, energy efficiency class spectrum A++ to E, nominal current 560 ... 560mA, lamp power 8 ... 8W, type of voltage DC, luminous flux 1400 ... 1400lm, rated luminous flux according to IEC 62722-2-1 1400lm, color rendering index CRI 80-89, lamp shape tube, double base, version glass/cover clear, light color according to EN 12464-1 neutral white 3300 to 5300 K, base B22d, color white, Light color 840 ... 840, color temperature 4000 ... 4000K, housing color white, color consistency (McAdam ellipse) SDCM3, dimmable, length 550mm, protection class (IP) IP20, weighted energy consumption in 1,000 hours 9kWh, average nominal service life 50000h, LED illuminant RIDI L-TUBE-B, color rendering Ra >= 80, color location tolerance < 3 Step Mac Adam (initial). LED modules designed as a linear circuit board. Mid-power LEDs for even illumination and maximum efficiency. Basic profile made of extruded solid aluminum for optimal thermal management. Linear plate twisted continuously over the entire length with the basic profile. Cover made of clear, frosted or opal PMMA for efficient light emission, end cover made of robust PC, colour-coordinated with the cover. Operation with an external LED driver (installed in the light), constant current, safety extra-low voltage of less than 60 volts (SELV-compliant). L-TUBE-B packaged. Length 550 mm, power consumption 8 watts. Color rendering Ra > 80. Light color 3000 (...830...), 4000 (...840...) or 6500 Kelvin (...865...). Installation: Factory installation in industrial and sports hall lights from the RIDI range. Tool-free, mechanical lamp replacement of the L-TUBE-B by releasing the snap-in connection of the spring steel clip on the connection side and shifting it on the long side and electrically via the socket-plug system.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

