

Item Number EB16521130

https://www.eibabo.in/merten/wiser-dimming-actuator-1-way-up-dimming-actuator-bus-system-14...200 w-meg5010-0001-eb16521130



Wiser dimming actuator 1-way UP - Dimming actuator bus system 14...200W MEG5010-0001

×

Merten

MEG5010-0001 4042811217235 EAN/GTIN

6785,24 INR excl. VAT**

plus **shipping**



16-17 days* (IND)

Wiser dimming actuator 1-fold UP MEG5010-0001 radio bus system, other bus systems, radio bidirectional, dimming actuator version, flush-mounted installation, with bus coupling, extension input, with LED display, number of outputs 1, output power 14 ... 200W, load type universal and LED retrofit, voltage 220 ... 240V, frequency 50 ... 60Hz, degree of protection (IP) IP20, min. depth of the device box 23mm, the Wiser dimming actuator 1gang UP switches and dims ohmic, inductive or capacitive loads. Depending on the application, the actuator is controlled in different ways. On-site operation: The actuator can be controlled with a maximum of 10 mechanical buttons in parallel operation. Room control: Within a room, the actuator can be controlled directly via the smartphone (with the Wiser app) or by another Wiser device (the Wiser app is not required). House control: Within a building, the actuator can be controlled via the Internet with a smartphone (with the Wiser app). The Wiser Home Touch control unit is also required for this. When installing the actuator in combination with a mechanical button, a correspondingly deep installation box must be used. With screw terminals. Functions: -Thermal protection, overload-proof, short-circuit-proof. -Soft start, soft stop. leading edge or trailing edge. The actuator and use additional functions, such as B.: -Set min/max brightness. -Switchable to RL LED mode. -Manually set the LED operating mode. -Set switch-on brightness or memory function. -Activate timer. -Timer with Astro function. Without power reserve. -Time synchronization via app. Rated voltage: AC 220-240V 50/60Hz. Rated power: LED bulbs: 5-100VA (RC), 5-20VA (RL). Incandescent lamps: 14-200 W. Halogen lamps: 14-150 W (230 V). 14-150 VA (NV with dimmable wound transformer). 14-200 VA (NV with dimmable electronic transformer). Dimming channels: 1. Neutral conductor: not required. Standby: max. 0.4 W. Connection terminals: screw terminals for max. 2x2.5 mm2. Extensions: max. 10 mechanical buttons. Protection: 16 A ci

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500.000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

