



Universal automatic switch - Movement sensor 15m CD 17281 GR



Jung
CD 17281 GR
4011377168251 EAN/GTIN

6655,43 INR excl. VAT**
plus shipping

 16-17 days* (IND)

Universal CD 17281 GR automatic switch, motion detector version, flush-mounted installation, networkable, creep-under protection/rear field monitoring, installation height 2.2m, max. range to one side 11m, max. frontal range 15m, detection field diameter on the floor 12m, response sensitivity adjustable, response brightness adjustable, Teach function for response brightness, dimming function with dimming insert, plastic material, thermoplastic material quality, halogen-free, suitable for degree of protection (IP) IP44, operating mode switch, min. switch-on time 2s, max. switch-on time 2min, horizontal detection angle 180 ... 180°, color grey, RAL number (similar) 7038, universal automatic switch, lens type 2.20 m, shatterproof, detection angle: 180°, detection area: tangential movements approx. 22 x 15 m and radial movements approx. 10 x 18 m, brightness setting: approx. 5 to 500 lx and day mode, sensitivity: off, 25 to 100%, follow-up time: dynamic, 10 s to 60 min, operating mode switch for A Automatic mode, permanently on or permanently off, LED display of the set operating mode, hotel function, night light function, presence simulation, alarm function, programming of up to 16 individual switching times, installation height: 2.20 m, extension of the detection area in combination with a 3-wire extension, adjustable sensitivity and brightness threshold, detection area can be restricted with a cover, setting the sensitivity of individual motion sensors in the device to influence the overall sensitivity, settings via smartphone and Clever Config app, indoor use, ambient temperature: - 5 to + 45 °C, for LB management Light inserts item no.: 1701 SE, 1704 ESE, 1710 DE, 1711 DE, 1713 DSTE, 1723 NE and 1708 IE, for automatic switching of lighting, depending on heat movement and ambient brightness, operation with flush-mounted insert for switching or dimming or 3-wire extension to expand the detection field

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

