



Ceiling monitor/presence detector DWPM 17360 AL



Jung
 DWPM 17360 AL
 4011377167025 EAN/GTIN

8031,20 INR excl. VAT**
 plus shipping

 16-17 days* (IND)

Ceiling monitor/presence detector DWPM 17360 AL Presence detector version, sensor type other, forced switch-off, scanning angle 360°, optimal installation height 3m, max. range to one side 10m, max -Function for response brightness, suitable for ceiling mounting, mounting type surface-mounted, connection type other, material metal, material quality aluminium, halogen-free, color aluminium, type of voltage AC, frequency 50 ... 60Hz, nominal voltage 230V, switch-off delay 120s, horizontal detection angle 360 ... 360°, response brightness 5 ... 1000lx, max. switching capacity 2300W, suitable for C-load, temperature -5 ... 45°C, max. inrush current 16A, extension input, alarm function, depth 66mm, diameter 103mm, ceiling monitor/presence detector, detection angle: 360°, detection range: tangential movements Ø approx. 20 m and radial movements approx. 16 m, brightness adjustment : approx. 5 to 2000 lx and daytime operation, sensitivity: off, 25 to 100%, run-on time: dynamic, approx. 10 s to 60 min, short-time operation: pulse duration: approx. 0.5 s, pulse pause approx. 0.3 s, Can be used as a guard and as a presence detector, constant light control in combination with a dimming insert, 2-point light control in combination with a switching insert, LED display of the set operating mode, hotel function, night light function, presence simulation, alarm function, programming of up to 16 individual switching times, Mounting height 3 m, setting the sensitivity of individual motion sensors in the device to influence the overall sensitivity, settings via smartphone and Clever Config app, indoor ceiling mounting, ambient temperature: - 5 to + 45 °C, dimensions (Ø x D):: 103 x 66 mm, for LB management inserts light art. nos.: 1701 SE, 1704 ESE, 1710 DE, 1711 DE, 1713 DSTE, 1723 NE and 1708 IE, for automatic switching of lighting, depending on heat movement and Ambient brightness, operation with flush-mounted insert for switching or dimming or 3-wire extension to expand the detection field

YOUR ADVANTAGES



WORLDWIDE TRADE
 Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
 > 500,000 customers worldwide



DHL TRACK & TRACE
 Shipment tracking



COMPLAINTS HANDLING
 Obliging and 100% safely



25 YEARS OF EXPERIENCE
 In worldwide mail order



ORDER LIVE CHAT
 With order history



SHORT DELIVERY TIME
 Warehousing



REFUND
 Within 14 days



DATA PROTECTION
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
 eibabo® electronics cheap online order
 eibabo® electric appliances buy online

