



Surge relay 4-channel FSR14-4x



Eltako
FSR14-4x
30014001
4010312313701 EAN/GTIN

4211,72 INR excl. VAT**
plus shipping

 **5-6 days* (IND)**

Impulse switching relay 4-channel FSR14-4x radio bus system, other bus systems without, radio bidirectional, REG mounting type, width in modular units 1, max. switching capacity 1000W, output power 1000W, suitable for C-load, max. number of switching outputs 4, max. Switching current 4A, rated current 16A, rated operating voltage 12... 12V, with bus coupling, removable bus module, modular expansion option, degree of protection (IP) IP20, surge switching relay with 4 channels, 1 NO contact each 4A/250V AC, 1000W bulbs, electrically isolated from the supply voltage, with DX technology. Bidirectional. Standby loss only 0.1 watts. Connection to the Eltako RS485 bus. Bus cross-wiring and power supply with jumper. Simply connect the N conductor to terminal (N) and L to K(L). This results in an additional standby loss of just 0.1 watts. If all 4 relays of the FSR14-4x are switched on, 0.7 watts are required. If the supply voltage fails, the system is switched off in a defined manner. The channels can be taught in independently of each other as ES and/or ER channels. Scene control: Several channels of one or more FSR14-4x for one scene each can be switched on or off with one of the four control signals of a button with double rocker taught in as a scene button. Central commands on the PC are sent with the wireless building visualization and control software GFVS. To do this, teach in one or more FSR14-4x on the PC. The buttons are taught in with the rotary switches and the 4 channels are tested if necessary. The LED under the upper rotary switch accompanies the teach-in process according to the operating instructions and indicates control commands during operation by flashing briefly.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

