



KNX presence detector Mini Universal, alpine white 3361-1 M WW



Jung
3361-1 M WW
4011377127548 EAN/GTIN

13381,07 INR excl. VAT**
plus shipping



5-6 days* (IND)

KNX presence detector Mini Universal alpine white 3361-1 M WW KNX bus system, presence detector design, surface-mounted type of installation, material plastic, other surface, design of the surface glossy, color white, RAL number (similar) 9016, with bus coupling, response brightness adjustable, optimal installation height 3m, Max. range to one side 6m, Max. frontal range 2.5m, detection field diameter on the floor 12m, vertical detection angle 0 ... 80°, horizontal detection angle 0 ... 360°, number of channels 2, KNX presence detector Mini Universal, with integrated bus coupler, integrated brightness sensor and integrated temperature sensor, ETS product family: physical sensors, product type: motion detector, nominal voltage KNX: DC 21 to 32 V SELV, 3 PIR sensors, detection field: 360°, range (Ø, mounting height 3 m) : approx. 12 m for walking people and approx. 7 m for sitting people, integrated brightness sensor, use as presence detector, motion detector or for signaling operation, output Primary functions: switching, staircase function, switching with forced position, value transmitter, light scene extension, operating mode specification for room temperature controller, detection area can be expanded by connecting several devices in parallel as main and extension, integrated temperature sensor, manual operation with IR remote control possible (item no.: KNX PM FB IR), 5 function blocks for motion or presence detection, each with 2 outputs, switchable function blocks, e.g. for day/night mode, PIR sensors can be evaluated separately, brightness sensor function with 3 limit values, daylight-dependent light control with a maximum of 3 channels, setpoint shift during operation, separate configuration of control and reduction phase, light control can be combined with presence detector function, bus connection: connection terminal, relative Humidity: 10 to 100%, no condensation, ambient temperature: - 5 to + 45 °C, storage and transport temperature: - 5 to + 45 °C, protection class: III

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

