


**KNX push button sensor 3 Plus 2-fold pure white  
2042112**


**Gira**  
 2042112  
 4010337081920 EAN/GTIN

**20315,71 INR** excl. VAT\*\*  
 plus shipping



5-6 days\* (IND)

Push-button sensor 3 Plus 2-fold rws 2042112 bus system KNX, other bus systems without, mounting type flush-mounted, with theft/dismantling protection, number of actuation points 6, number of buttons 2, with LED display, with display, material plastic, material quality thermoplastic, other surface, Glossy surface design, color white, RAL number (similar) 9010, transparent, with room thermostat, degree of protection (IP) IP20, KNX push button sensor 3 Plus 2-fold pure white glossy Features: Installation on bus coupler 3 or bus coupler 3 external sensors. Dismantling protection by screwing. Graphic display with background lighting and a wide range of display options, e.g. B. temperature, time, date, alarm and information texts. White power LED. Multicolored status LED (red, green, blue) configurable via the ETS. Internal temperature sensor to measure the local room temperature. Pushbutton sensor properties: Rocker or button function can be set for each control surface. Rocker function: switching, dimming, shutter control, 1-byte value transmitter, 2-byte value transmitter, scene extension unit, 2-channel operation and manual fan control. Button function: switching, dimming, shutter control, 1-byte value transmitter, 2-byte value transmitter, scene extension, 2-channel operation, controller extension, controller operation, heating timer operation and manual fan control. Controller extension or controller operation: Operating mode changeover (defined selection of an operating mode or change between different operating modes for controller extension), change of the presence status, setpoint shift. Blocking object for blocking individual button or rocker functions. Display of an alarm message by flashing all LEDs. Multicolored status LED (red, green, blue) is configurable globally or individually. A higher-level function can be activated via the bus, whereby the color and display information of individual status LEDs can be changed depending on the priority. Operating LED ON, OFF, automatic switch-off or switchable via object. Communication object for brightness control of the status LED, labeling field lighting and background lighting of the display. Room temperature controller properties:: Operating modes: comfort, stand-by, night and frost or heat protection, each with their own temperature setpoints (for heating and/or cooling). Comfort extension through presence button. Frost or heat protection switchover by window status or by automatic frost protection. Display of the room temperature controller information via the device display. Either one or two control circuits. Different control types can be...

**YOUR ADVANTAGES**


**WORLDWIDE TRADE**  
 Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
 > 500,000 customers worldwide



**DHL TRACK & TRACE**  
 Shipment tracking



**COMPLAINTS HANDLING**  
 Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
 In worldwide mail order



**ORDER LIVE CHAT**  
 With order history



**SHORT DELIVERY TIME**  
 Warehousing



**REFUND**  
 Within 14 days



**DATA PROTECTION**  
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

**eibabo®** and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

**eibabo®** the Smart Home technology shop  
**eibabo®** electronics cheap online order  
**eibabo®** electric appliances buy online

