

## Item Number EB15705573

https://www.eibabo.in/abb/automatic-circuit-breaker-b-16a-1-pole-s201s-b16-eb15705573



## Automatic circuit breaker B 16A 1-pole S201S-B16



## ABB

S201S-B16 2CDS251002R0165 4016779709453 EAN/GTIN

217,37 INR excl. VAT\*\*

plus shipping



5-6 days\* (IND)

Automatic circuit breaker B 16A 1p 253V S201S-B16 tripping characteristic B, number of poles (total) 1, number of fused poles 1, rated current 16A, rated voltage 230V, rated insulation voltage Ui 440V, rated impulse withstand voltage Uimp 4kV, rated switching capacity Icn according to EN 60898 at 230 V 6kA, rated switching capacity Icn according to EC 60947-2 at 230 V 6kA, rated switching capacity Icu according to IEC 60947-2 at 230 V 6kA, rated switching capacity Icu according to IEC 60947-2 at 230 V 6kA, rated switching capacity Icu according to IEC 60947-2 at 2400 V 6kA, rated switching capacity Icu according to IEC 60947-2 at 230 V 6kA, rated switching capacity Icu according to IEC 60947-2 at 230 V 6kA, rated switching capacity Icu according to IEC 60947-2 at 2400 V 6kA, type of voltage AC, frequency 50... 60Hz, energy limitation class 3, overvoltage category 3, degree of pollution 2, Additional equipment possible, width in pitch units 1, installation depth 69mm, degree of protection (IP) IP20, ambient temperature during operation -25... 55°C, connectable conductor cross-section stranded 0... 25mm², connectable conductor cross-section solid 0... 35mm², the circuit breakers of the S 200S series protect cables and lines against overload and short circuits in accordance with DIN VDE 0100-430 and DIN V DE 0100-530. They meet the building regulations DIN VDE 0641-11 and IEC/EN 60898-1. The plug-in terminal on the outgoing side enables cables up to 4 mm² to be installed without tools. A voltage test can also be carried out with the cables connected at the test point provided. Its patented connection terminal ensures simple and safe contacting and handling by means of a pressure plate. For better visibility when wiring, the connection opening for cables is above the connection opening for the busbar. Conductor cross-sections up to 35 mm² can be connected directly to the device via the connection terminal with insulation in protection class IP20. The extensive range of accessories offers you everything you need for

## YOUR ADVANTAGES



**WORLDWIDE TRADE**Corporate video eibmarkt®



COMPLAINTS HANDLING
Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



**25 YEARS OF EXPERIENCE** *In worldwide mail order* 



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT
With order history



**DATA PROTECTION**Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- \*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- \*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

