

Item Number EB16516625

https://www.eibabo.in/hager/knx-switching-actuator-20x-or-blind-shutter-actuator-10-fold-txm620d-eb1 6516625

## KNX switching actuator 20x or blind/shutter actuator 10fold TXM620D



Hager TXM620D 3250616048782 EAN/GTIN

## 43009,86 INR excl. VAT\*\*

plus shipping



Switching/blind output KNX 20/10f,16A CLast TXM620D bus system KNX, other bus systems without, mounting type REG, width in modular units 10, local/manual operation, with LED display, number of binary inputs 0, max. switching capacity 28750W, output power 2300W, suitable for C-load, max. number of switching outputs 20, max. switching current 16A, rated operating voltage 230 ... 230V, different phases can be connected, with bus coupling, protection class (IP) IP20, switching/blind actuator 20/10 compartment KNX easy, 16A, C load. Switching/blind actuator REG for switching an independent load per actuator channel or controlling a blind drive via two actuator channels each, any combination of drive and switching functions. Modular installation device with integrated bus coupler, plug-in terminals for KNX bus connection, load/switch connections and labeling field. 10 control buttons (switching channel 1-10 and switching to channel 11-20) for manual operation per output with status LED (single surface operation). Auto/Manual slide switch, illuminated programming button. Functions: Control options for the switching channels for ON/OFF, time switch function with switch-off early warning and priority control with the respective status display. Automatic function can be deactivated/activated and load shedding through channel deactivation with the highest priority possible. 64 scene functions can be set per channel. Roller shutter/blind function in up/down mode with slat angle adjustment, positioning function and slat adjustment for blinds in percent parameterization. Status objects for the position of the slats in percent and the upper/lower end position. Forced control with status display and 3 alarm objects with different priority control. 64 scene functions set channel and adjustable sun protection function. Note: The device can be programmed using the easy commissioning tool, easy configuration server or the ETS (from version 4). Observe the instructions of the roller shutter/blind motor manufacturer.

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

