

**LED recessed light 3000K, DALI - Ceiling-/wall luminaire
1x29W 312367.002.76****RZB**
312367.002.76
4051859326595 EAN/GTIN**20530,43 INR** excl. VAT**
plus shipping bulky item **16-17 days* (IND)**

LED recessed luminaire 3000K, DALI 312367.002.76 Suitable for ceiling mounting, Suitable for recessed mounting, LED bulbs cannot be replaced, With bulbs, Suitable for number of bulbs 1, Other socket, Housing material aluminium, Housing color white, Cover material opal plastic, Design of the louvre without, type of voltage AC/DC, nominal voltage 220 ... 240V, control gear current-controlled LED control gear, with control gear, DALI dimming, dimming dependent on control gear, light distributor without, light distribution symmetrical, beam angle unshielded/diffuse, light emission direct, rated service life L70/B10 at 25 °C 50000h, degree of protection (IP) IP20, degree of protection (NEMA) other, impact resistance IK03, protection class II, rated ambient temperature according to IEC62722-2-1 5 ... 30°C, glow wire test according to IEC 60695-2-11 650 °C - 30 s, suitable for lamp power 29 ... 29W, max. system power 29W, rated luminous flux according to IEC 62722-2-1 3300lm, light color white, color temperature r 3000 ... 3000K, color rendering index CRI 80-89, luminous efficacy of luminaire 114lm/W, power factor 0.95, width 308mm, length 1245mm, installation length 1233mm, installation width 296mm, installation height/depth 160mm, type of wiring termination, number of poles 4, conductor cross-section 1.5mm², connection type plug-in terminal, highly economical series of lights with progressive LED technology, consisting of ceiling, wall, inlaid installation and pendant lights for interiors. Excellent for office areas (UGR 19) and computer workstations (BAP) in accordance with DIN EN 12464-1. Suitable for use in the food and beverage industry. Light guide and diffuser made of non-yellowing PMMA with fine microprismatics. RZB SIDE-LITE technology: Lateral light coupling for above-average homogeneous luminance distribution. LED service life 50,000 h (L70, B10). Flicker < 5%. Extremely simple converter installation thanks to the rotary plug-in system and extended converter connection cable to the light. Versions with smart+free Bluetooth control for wireless networking and operation using an Android / iOS device, free app available for download. Frame aluminum white powder-coated. Diffuser made of plastic (PMMA) opal. Diffuser and light guide made of non-yellowing plastic (PMMA). Lateral light coupling with LED. Bulbs (LED) included. Control gear external. +

YOUR ADVANTAGES**WORLDWIDE TRADE**
Corporate video eibmarkt®**99% CUSTOMER SATISFACTION**
> 500,000 customers worldwide**DHL TRACK & TRACE**
Shipment tracking**COMPLAINTS HANDLING**
Obliging and 100% safely**25 YEARS OF EXPERIENCE**
In worldwide mail order**ORDER LIVE CHAT**
With order history**SHORT DELIVERY TIME**
Warehousing**REFUND**
Within 14 days**DATA PROTECTION**
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

