



**LED pendant light 4000K - Pendant luminaire 1x17W
901685.002.1**



RZB
901685.002.1
4051859344827 EAN/GTIN

11866,46 INR excl. VAT**
plus shipping



16-17 days* (IND)

LED pendant light 4000K 901685.002.1 Energy efficiency class of the light source according to EU Regulation 2019/2015 not relevant, suitable for number of lamps 1, socket without, housing material other, housing color white, cover material opal plastic, design of the grid without, voltage type AC, Nominal voltage 220 ... 240V, nominal current 71 ... 77mA, LED nominal current at constant current 71 ... 77mA, control gear LED control gear current-controlled, with control gear, replaceable control gear, without dimming function, light distributor without, reflector without, light distribution symmetrical, color consistency (McAdam ellipse) SDCM4, light emission direct, rated service life L80/B10 at 25 °C 50,000h, luminous flux drop at average. Service life 50,000 h at 25 °C ambient temperature. 80%, failure rate at average Service life of 50,000 h at 25 °C ambient temperature. (tq) 50%, Protection class (IP) IP20, Protection class (NEMA) other, Impact resistance IK06, Protection class I, Glow wire test according to IEC 60695-2-11 650 °C - 30 s, Suitable for lamp power 17 ... 17W, Max. System power 17W, rated luminous flux according to IEC 62722-2-1 1800lm, light color white, luminaire luminous efficacy 106lm/W, color temperature 4000 ... 4000K, color rendering index CRI 80-89, glare limitation (UGR) 26.8, power factor 0.9, color temperature adjustable no, luminous flux adjustable no, beam angle adjustable no, height/depth 88.8mm, diameter 257mm, with suspension, pendant length 2000 ... 2000mm, type of wiring termination, number of poles 3, conductor cross section 1.5mm², connection type other, LED bulbs not replaceable, With bulb, flat cylindrical pendant light. Cylinder housing made of powder-coated sheet steel. Housing die-cast aluminum and powder-coated sheet steel. Cover ring made of die-cast aluminum, powder-coated. Canopy powder-coated sheet steel. Diffuser and light guide made of non-yellowing plastic (PMMA) opal matt. Suitable for pendulums. Transparent pendulum cable 2 m, can be shortened. Mounting rings for subsequent installation of a fabric shade available as an accessory.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

