



Switch disconnector 3LD3 lu 32A - Safety switch 4-p 3LD3240-1TL11



Siemens
3LD3240-1TL11
 4001869550992 EAN/GTIN

3457,88 INR excl. VAT**
 plus shipping



16-17 days* (IND)

Switch disconnector 3LD3 lu 32A 3LD3240-1TL11 Design as a main switch Design as a maintenance/repair switch Design as a safety switch Number of switches 1 Max at AC-21, 400 V 32A, rated operational power at AC-3, 400 V 9.5kW, rated short-time withstand current I_{cw} 0.5kA, number of poles 4, number of auxiliary contacts as NC contact 1, number of auxiliary contacts as NO contact 1, number of auxiliary contacts as changeover contact 0, Device design Built-in device Fixed installation technology, Suitable for central front mounting, Suitable for distribution board installation, Suitable for intermediate installation, Color of the actuating element black, Design of the actuating element toggle, Lockable, Main circuit connection type box terminal, Degree of protection (IP), front IP65, degree of protection (NEMA) other, 3LD3 switch disconnectors, lu 32 A main switch 3-pole + N rated operational power at AC-2 3 A at 400V 11.5kW Floor mounting Basic switch with door coupling Central hole mounting 22.5mm Toggle drive black 48x48mm with auxiliary switch 1OE+1S The 3LD main and emergency stop switch for safe disconnection of loads in a wide variety of environments. The possible uses of the 3LD3 line disconnectors are diverse. After disconnection from the mains, they ensure that all electrical equipment is safely isolated, switching, for example, three-phase motors, but also air conditioning and ventilation systems. 3LD3 are also predestined for the use of control or switching cabinets, especially for applications in small machines (e.g. saws, compressors, pumps, cement mixers, drills, milling machines and woodworking machines). The main features of the Siemens 3LD main and emergency stop switches are: 1. Modular design, quick and easy installation of auxiliary switches, N-PE terminal or 4th pole. 2. Versatile in use thanks to local approvals. 3. One mechanical size for five electrical sizes. 4. Can be used for direct current applications. 5. Types of mounting: front mounting, mounting plate, DIN rail. 6. Optimum mains separation from 16 A to 63 A thanks to the lockable rotary drive. For the safe, efficient electrical infrastructure in buildings and industry, Siemens offers an integrated portfolio of protective switching, measuring and monitoring devices, distribution systems, switches and socket outlets.

YOUR ADVANTAGES



WORLDWIDE TRADE
 Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
 > 500,000 customers worldwide



DHL TRACK & TRACE
 Shipment tracking



COMPLAINTS HANDLING
 Obliging and 100% safely



25 YEARS OF EXPERIENCE
 In worldwide mail order



ORDER LIVE CHAT
 With order history



SHORT DELIVERY TIME
 Warehousing



REFUND
 Within 14 days



DATA PROTECTION
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
 eibabo® electronics cheap online order
 eibabo® electric appliances buy online

