



## Circuit breaker 3VA2 IEC Frame 400 3VA2340-5JQ42-0BC0

**Siemens**  
3VA2340-5JQ42-0BC0  
4042949069997 EAN/GTIN

**246005,82 INR** excl. VAT\*\*  
plus shipping



16-17 days\* (IND)

Circuit breaker 3VA2 IEC Frame 400 3VA2340-5JQ42-0BC0 Rated uninterrupted current  $I_u$  400A, rated voltage 690 ... 690V, rated limiting short-circuit breaking current  $I_{cu}$  at 400 V, 50 Hz 55kA, overload release current setting 160 ... 400A, setting range of the short-time delayed short-circuit release 240 ... 4000A, setting range of the instantaneous short-circuit release 600 ... 4000A, connection type main circuit screw connection, device design built-in device fixed installation, suitable for DIN rail mounting, DIN rail mounting optional, number of auxiliary contacts as NC contact 0, number of auxiliary contacts as NO contact 0, number of auxiliary contacts as changeover contact 2, with undervoltage release, number of poles 4, position of the connection for the main circuit at the front, design of the toggle lever actuating element, complete device with protective unit, optional motor drive, degree of protection (IP) IP40, circuit breaker 3VA2 IEC Frame 400 switching capacity class M  $I_{cu}=55kA$  @ 415V 4-pole, system protection ETU560, LSIG,  $I_n=400A$  overload Protection  $I_r=160A$ ...400A Short-circuit protection  $I_{sd}=0.6...10 \times I_n$ ,  $I_i=1.5 \times I_n$  N-conductor protection adjustable (OFF, up to 100%) Ground fault protection, switchable  $I_g=0.2...1 \times I_n$   $t_g=0.05-0.8s$  Screw flat connection Undervoltage release (UVR) 24V DC 2 auxiliary switches HQ molded case circuit breakers 3VA2 with ETU 5 series for system protection. The 3VA molded case circuit breakers from Siemens, as an important part of the SENTRON protective components for industrial applications and for applications in the infrastructure sector, offer effective starter and motor protection for systems through safe shutdown in the event of overload and short circuits. The 3VA molded case circuit breakers set standards in terms of flexibility and modular variety of accessories. Uniform accessories for several sizes across all series of 3VA1 and 3VA2 molded case circuit breakers. This variant of the 3VA molded case circuit breaker is primarily characterized by: 1.Compact design. 2. Available as a variant for system protection and generator protection. 3. Available in 3 and 4 pole versions. 4. Four switching capacity classes from 55 kA ... 150 kA at 415 V. 5. Depending on the size: rated current 25 A...630 A. 6. Installation in permanent, plug-in technology, slide-in technology possible. 7. Outstanding selective protective behavior in the rated operating current distance 1:2.5 and 1:1.6. 8. The series has an electronic overcurrent release. 9. Has an integrated display for showing the measured values. 10. Optional communication connection via Modbus TCP, Modbus RTU,...

### YOUR ADVANTAGES



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

