



Fan 1850 cbm/h, 90W, IP55 - Two-way industrial fan 300mm EZQ 30/4 B



Maico
EZQ 30/4 B
0083.0106
4012799831068 EAN/GTIN

62453,06 INR excl. VAT**
plus shipping

 5-6 days* (IND)

Fan 1850cbm/h, 90W, IP55 EZQ 30/4 B Mains frequency 50Hz, rated voltage 230V, conveyor temperature 60 ... 60°C, volume flow 1850m³/h, speed 14251/min, protection class (IP) IP55, ventilation version, Nominal width 300mm, closure flap without, protective grille on the suction side, yellow chromated, contact protection according to DIN EN ISO 13857. 8-blade impellers made of glass fiber reinforced polyamide. Dynamically balanced in 2 levels, in accordance with quality level 6.3, DIN ISO 1940, Part 1. Installation possible in any position. Conveying direction: The following figure shows the conveying direction: Conveying direction A: Suction via the motor, standard. Conveying direction B: Blowing via the motor, on request. Direction of rotation, reversing operation: The volume flow decreases by approx. 35% if the conveying direction is abnormal. Motor: asynchronous motor. Speed controllable. Exception: Type EZQ 45/6 B, EZS 45/6 B, DZQ 40/2 B and DZS 40/2 B. Reversible. Exception: Fans with shaded-pole motors (...-E). Not suitable for pumping air saturated with water vapor. AC motor: EZQ and EZS series. Rated voltage 230 V, 50 Hz. Thermal overload protection as standard. Fans ..B: Capacitor motors with operating capacitor on the protective grille or on the wall sleeve, protection class IP 55. Fans ..D: Capacitor motors with operating capacitor in the connection box, protection class IP 54. Fans ..E: Shaded pole motors, not reversible, protection class IP 54 .Electrical connection: To the terminal strip in the end cover of the motor. Safety instructions: The fan may only be put into operation if the impeller is protected against contact in accordance with DIN EN ISO 13857. Article: EZQ 30/4 B, version: Square wall plate, delivery volume: 1850 m³/h, speed: 1425 1/min, impeller type: axial, speed controllable: yes, reversibility: yes, voltage type: alternating current, rated voltage: 230 V, mains frequency: 50 Hz, nominal power: 90 W, Irated: 0.4 A, IMax: 0.55 A, protection class: IP 55, thermal class: B, installation location: wall / ceiling, installation type: surface-mounted, installation position: horizontal / vertical, material: sheet steel , galvanized, weight: 7.9 kg, nominal width: 300 mm, width: 465 mm, height: 465 mm, depth: 240.5 mm, conveyor temperature at nominal current: -20 °C to 60 °C, conveyor temperature at IMax: - 20 °C to 60 °C, closure flap: without

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

