

AEG

Item Number EB14200474

×

https://www.eibabo.in/eht-aeg/flow-heater-switchable-instantaneous-water-heater-24kw-aeg-ddleoektd 18-21-24-eb14200474

Flow heater switchable - Instantaneous water heater 24kW AEG DDLEÖKTD18/21/24

EHT AEG AEG DDLEÖKTD18/21/24 222398 4041056022826 EAN/GTIN

54370,93 INR excl. VAT**

plus shipping



Switchable instantaneous water heater AEG DDLEÖKTD18/21/24 energy efficiency class A, energy efficiency class spectrum A to G, material of the pressure vessel plastic, nominal capacity 0.4I, max. permissible operating pressure 10bar, nominal power 24kW, nominal voltage 1 380V, nominal voltage 2 415V, manual operation, digital temperature display, With display, mounting type above/under the table, electronic output control, connected load 18 ... 24kW, bare wire heating system, safety shut-off pressure shut-off, degree of protection (IP) IP25, connection for cold drinking water external thread, nominal inside diameter for cold drinking water 1/2 inch (15), pipe outside diameter for cold drinking water 21.5mm, connection hot water external thread, nominal inside diameter for cold drinking water 1/2 inch (15), pipe outside diameter to display. Sitable for plastic pipe, suitable for preheated water, type of control electronically, height 485mm, width 226mm, depth 93mm, weight 3 ,8kg, instantaneous water heater, fully electronically controlled, for sale Supply of washbasin, kitchen sink, shower, bathtub. Precise temperature selection using a 2-color backlit, easy-to-read multifunction display. Display of temperature, flow rate, energy consumption and time. Two memory buttons for individually adjustable temperature selection for the next tapping process. Heating block made of glass fiber reinforced polyamide. 4 heating coils lying directly in the water. Measuring turbine for precise flow rate measurement. Electronic air bubble detection. Process-controlled motor valve for precise water temperature at maximum flow rate. Temperature selection from 30 °C to 60 °C. Integrated diagnostic system. Suitable for inlet temperatures up to a maximum of 0°C (e.g. solar preheated water). Connection options for long-distance and direct tapping. For connection to plastic pipe installations with DVGW test mark. Easy assembly with separate mounting plate and quick release, with assembly template, hood disassembly from the front, withou

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

