
×



Item Number EB15504884

https://www.eibabo.in/wago/knx-module-knx-fieldbus-function-technology-module-753-646-eb1550488



KNX module - KNX fieldbus function-/technology module 753-646

WAGO

753-646 4045454778033 EAN/GTIN

30240,02 INR excl. VAT**

plus **shipping**



16-17 days* (IND)

KNX/EIB module 753-646 Number of HW interfaces Industrial Ethernet 0 Number of interfaces PROFINET 0 Number of HW interfaces serial RS-232 0 Number of HW interfaces serial RS-422 0 Number of HW interfaces serial RS-485 0, number of HW interfaces serial RS-422 0 Number of HW interfaces serial RS-485 0, number of HW interfaces serial RS-485 0, number of HW interfaces serial RS-485 0, number of HW interfaces USB 0, number of HW interfaces USB 0, number of HW interfaces other 0, supports protocol for KNX, supports protocol for other bus systems, system components, degree of protection (IP) IP20, fieldbus connection via separate bus coupler possible, DIN rail mounting possible, explosion protection category for gas without, explosion protection category for dust without, width 12mm, height 64mm, depth 100mm, the KNX /EIB/TP1 bus terminal is used to connect to a KNX/EIB/TP1 network. The terminal supports two different functions: Device mode: The terminal enables the connection of the programmable controller (*1) relevant for building automation to a KNX/TP1 network. In a KNX network, the terminal appears as a standard KNX device and is integrated via the ETS3/4 Professional commissioning tool. The terminal supports a maximum of 253 communication objects with any DPTs, 254 group addresses and 254 associations. The assignment of data from the application program to group addresses is carried out via an ETS3/4 plug-in. Router mode: In combination with the KNX IP controller and the first inserted KNX/EIB/TP1 module, the device becomes a KNXnet/IP router. The changeover of the terminal to router mode takes place automatically. An application program is not required for operation in router mode. Other terminals lined up on the KNX IP controller are addressed by the application in device mode. An external KNX power supply and the ETS3/4 Professional are required to operate the KNX/EIB/TP1 bus terminal.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLING Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE



In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

