

Item Number EB16514737

×

https://www.eibabo.in/berker/push-button-sensor-1x-black-glass-knx-touch-sensor-2-fold-75161592-eb 16514737



Push button sensor 1x black glass - KNX touch sensor 2fold 75161592

Berker 75161592 4011334372066 EAN/GTIN

9508,56 INR excl. VAT\*\*

plus **shipping** 



Push-button sensor 1-fold glass black 75161592 bus system KNX, other bus systems without, type of installation flush-mounted, with theft/dismantling protection, number of actuation points 2, number of buttons 1, with LED display, material glass, material quality other, surface lacquered, surface finish glossy, Color black, RAL number (similar) 9005, degree of protection (IP) IP20, push button sensor 1 gang comfort B.IQ glass, black. Push-button sensor 1-fold comfort B.IQ with disassembly protection, with one operating and two status LEDs. Flush installation. The push-button comfort 1-way is an instabus user module. It is used to plug onto a bus coupler Up. Dismantling protection is provided by screwing the push button sensor to the flush-mounted bus coupler. The data exchange between the push button sensor and the bus coupler takes place via the user interface (AST). Every button press on the 1-gang push button sensor causes the bus coupler to generate a telegram and send it to the bus. The telegram format depends on the parameterization of the application. Depending on the selected parameterization, switching, dimming, blind and value transmitter functions can be combined as desired. Application properties: Button functions: Buttons, switching, switching in toggle mode, dimming one/two-surface operation, blind control one/two-surface operation, value transmitter/light scene extension with value transmitter 1-byte function, light scene recall with/without memory function, brightness value transmitter, temperature value transmitter, value transmitter 2 Byte, cyclic sending, control function, forced operation. Additional functions: Two operating levels with selectable functionality, switchover of operating levels via object. LED: Status LED per button, operation LED. Protection against dismantling: with mechanical protection against dismantling, with software-controlled protection against dismantling.


## YOUR ADVANTAGES





> 500,000 customers worldwide 25 YEARS OF EXPERIENCE

99% CUSTOMER SATISFACTION





**DHL TRACK & TRACE** Shipment tracking

ORDER LIVE CHAT With order history

DATA PROTECTION Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

