

Item Number EB17203536

27.04.2024/16:54

×

https://www.eibabo.in/zumtobel/led-recessed-ceiling-light-ep-1200-840-evg-ceiling-wall-luminaire-mirel-I-mi-42183524-eb17203536



## LED recessed ceiling light EP 1200-840 EVG - Ceiling-/wall luminaire MIREL-L mi #42183524

Zumtobel MIREL-L mi #42183524 42183524 9008709753433 EAN/GTIN

## 12080,59 INR excl. VAT\*\*

plus shipping

b 5-6 days\* (IND)

LED recessed ceiling light EP 1200-840 EVG MIREL-L mi 42183524 Suitable for ceiling mounting, Suitable for recessed mounting, LED bulbs cannot be replaced, With bulbs, Suitable for computer workstations according to EN 12464-1, Suitable for number of bulbs 1, Other socket, Housing material plastic, Housing color white, design of the louvre without, type of voltage AC, nominal voltage 220 ... 240V, control gear current-controlled LED control gear, with control gear, without dimming function, light distribution symmetrical, light emission direct, rated lifespan L70/B50 at 25 °C 100000h, rated lifespan L80/B50 at 25 °C 66000h, rated service life L90/B50 at 25 °C 33000h, degree of protection (IP) IP20, protection class II, max. system power 10.7W, rated luminous flux according to IEC 62722-2-1 1190lm, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, power factor 0.83, width 170mm, height/depth 38mm, length 170mm, installation height/depth 33mm, LED recessed ceiling light with lens op tik. Luminaire output: 10.7 W, with LED converter, LED service life 50,000 hours until the luminous flux drops to 85% of the initial value. Color tolerance (initial MacAdam): 3. Luminaire luminous flux: 1190 lm, luminaire luminous efficacy: 111 lm/W. Color rendering Ra > 80, color temperature 4000 K. Light control via square lens optics for maximum luminaire efficiency, perfect glare control and batwing light distribution. Luminaire housing made of polycarbonate (PC) painted in white, suitable for plasterboard ceilings, tool-free installation using two fastening springs for ceiling thicknesses of 1-25 mm. With strain relief and plug-in terminal. Luminaire wired halogen-free, dimensions: 170 x 170 x 38 mm, weight: 1 kg

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

