



Glass sensor 2-fold with room temperature controller Ber - KNX touch sensor 6-fold 75642035



Berker
75642035
4011334317883 EAN/GTIN

42143,93 INR excl. VAT**
plus shipping



16-17 days* (IND)

Glass sensor with room temperature. 75642035 KNX bus system, Other bus systems without, Flush mounting type, With theft/dismantling protection, With bus coupling, Number of actuation points 6, Number of buttons 0, With LED display, With display, Material glass, Material quality other, Surface other, Surface finish Glossy, color black, RAL number (similar) 9005, with room thermostat, degree of protection (IP) IP20, min. depth of device box 27mm, glass sensor 2-fold with temperature controller TS sensor, black. Double glass sensor with all-round bevel, without visible fastening elements, with four control surfaces, LED display with symbols for showing the operating mode, controller lock, room outside temperature, time (timer required), with 2 additional display sensor surfaces, with a blue operating -LED, with four white status LEDs, flush-mounted installation, special program. Operating element for room-related and room-spanning control of functions. For individual individual room temperature control, actuation by touching the glass plate (capacitive detection), flat design and high switching reliability thanks to the conductor tracks being applied directly to the glass plate, for installation in a special installation box for flush-mounting and hollow walls, height and side compensation for installation in a special installation box, with Adapter ring for dismantling protection and shadow gap formation. For vertical installation, with removal tool, with integrated bus coupler, bus connection via connection terminal. The scope of the display menu for operation can be parameterised. For switch pushbutton dim blind room temperature controller functions, value transmitter for dimming position brightness and temperature values 1 and 2 bytes, one and two surface operation configurable, sensor surfaces can be blocked via object, controller operating modes: comfort standby night and frost/heat protection mode. For heating and/or cooling operation with/without additional stage, control parameters for heating or cooling elements are preset. For continuous (PI) or switching (2-point) control, temperature measurement via internal and/or external, connectable sensors with averaging, message objects for heating and cooling, with valve protection function, object for controller status, with key lock function.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

