

Item Number EB14200279

https://www.eibabo.in/eht-aeg/open-storage-tank-5-liters-2kw-boiler-electric-aeg-huz5oeko-dropstop-eb14200279



Open storage tank 5 liters 2kW - Boiler electric AEG Huz5ÖKO DropStop

×

EHT AEG

AEG Huz5ÖKO DropStop 222167 4041056023151 EAN/GTIN

11906,10 INR excl. VAT**

plus shipping



5-6 days* (IND)

Open small storage tank 5 liters 2kW AEG Huz5ÖKO DropStop energy efficiency class A, energy efficiency class spectrum A to G, material of the boiler plastic, material jacket plastic, volume of the container 5l, nominal power 2kW, connection voltage 230 ... 230V, frequency 50 Hz, embodiment under the table, applicable at normal water pressure, warm-up time from 10 °C - 65 °C 10 min, tapping capacity at 60 °C, continuous operation 5l/min, wall installation, vertical placement, temperature limitation, max. permissible operating pressure 0bar, height 420mm, width 263mm, depth 230mm, connection cold Drinking water external thread, nominal inner diameter of cold drinking water 3/8 inch (10), connection hot water external thread, connection tap connection external thread, protection class (IP) IP24, energy efficiency hot water 88%, tapping profile XXS, small storage tank, capacity 5 litres, for under-table installation, which no longer works when heating up dripping. With ThermoStop technology. Modern, attractive design. Stepless temperature selection from approx. 35 °C to 85 °C. Temperature selection limitation on the rotary knob to 45 °C / 55 °C / 65 °C possible. Outstanding thermal insulation, stand-by power consumption of only 0.20 kWh/24h. Metal water fittings. Safety temperature limiter that can be reset by pulling the mains plug. Connection cable with safety plug, approx. 0.6 m. VDE/GS mark, radio protection mark/EMC. Danger! Application note: This article is a pressureless device (maximum permissible operating pressure = 0 bar). It can only be used with non-pressurized fittings (low-pressure fittings). Please note the difference between high pressure and low pressure fittings. The high-pressure faucet mixes the water inside the faucet. The low-pressure fitting is connected to a water tank (boiler) and has 3 connections. When the water is heated in the storage tank, it expands, which can lead to dripping in the fitting.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLING Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

