

×

https://www.eibabo.in/stiebel-eltron/wall-tank-white-150l-white-boiler-electric-hfa-z-150-eb14208403



Wall tank white 150L white - Boiler electric HFA-Z 150

Stiebel Eltron HFA-Z 150 073114 4017210731149 EAN/GTIN

76765,53 INR excl. VAT**

plus shipping bulky item



Wall storage tank ws 150L white HFA-Z 150 energy efficiency class C, energy efficiency class spectrum A to G, boiler material steel, jacket material steel, volume of the container 150l, rated output 6kW, connection voltage 230 ... 400V, three-phase version, frequency 50 Hz, hanging version, With off-peak mode, can be used with normal water pressure, warm-up time from 10 °C - 65 °C 90 min, tapping capacity at 60 °C, continuous operation 18 l/min, wall installation, vertical placement, temperature limitation, max. permissible operating pressure 6 bar, protective anode, height 1280 mm, width 510mm, depth 510mm, cold drinking water connection male thread, nominal inside diameter cold drinking water 1/2 inch (15), pipe outside diameter cold drinking water 21.5mm, hot water connection male thread, nominal inside diameter hot water connection 1/2 inch (15), pipe outside diameter cold drinking mater 21.5mm, connection female thread, tap connector nominal ID 1/2 in. (15), pipe OD drain connector 21.5mm, depth 510mm, cold strade thread, not water supply. –Closed (pressure-resistant) to supply several tapping points. Installation also in connection with plastic pipe systems (observe manufacturer's information and application limits). -Open (non-pressurized) to supply a tapping point. - Boiler operation also possible. Steel inner tank with special enamel and anti-corrosion rod, thermal insulation with low heat loss. Heating flange dual circuit/single circuit operation. The water content is kept at the set temperature depending on the controller (depending on the selected connection). With boiler operation, the water content is heated once and the heating process must be switched on manually. Infinitely variable temperature setting from approx. 35 degrees C to approx. 82 degrees C possible. Automatic frost protection for single-circuit operation. Signal lamp for boiler operation and rapid heating (once by push button, remote control on site), exchangeable copere hating flange with drain connection. Installation with: Safety

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL). ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries

outside the EU. *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

