


Storage tank 300l 6bar - Boiler electric SHW 300 S

Stiebel Eltron

SHW 300 S

182121

4017211821214 EAN/GTIN

166097,26 INR excl. VAT**

plus shipping bulky item



16-17 days* (IND)

Freestanding storage tank 300l 6bar SHW 300 S energy efficiency class C, energy efficiency class spectrum A to G, boiler material steel, jacket material steel, volume of the container 300l, rated output 6kW, connection voltage 230 ... 400V, three-phase version, frequency 50/60 Hz, version floor model, With off-peak mode, can be used with normal water pressure, warm-up time from 10 °C - 65 °C 180 min, tapping capacity at 60 °C, continuous operation 38 l/min, vertical placement, with temperature display, temperature limitation, with circulation connection, max. permissible operating pressure 6 bar, with thermometer, protective anode, height 1593mm, width 700mm, depth 815mm, connection cold drinking water external thread, nominal inside diameter cold drinking water 1/2 inch (15), pipe outside diameter cold drinking water 33.7mm, connection hot water external thread, nominal inside diameter hot water connection 1/2 inch (15), pipe outside diameter Warm drinking water 33.7 mm, nominal inner diameter of circulation line 1/2 inch (15), protection class (I P) IP24, energy efficiency of hot water 39%, tapping profile XL, closed hot water tank (pressure-resistant) made of steel, special enamel on the inside and anti-corrosion rod for the hot water supply of several tapping points in the home, business and agriculture, also in connection with plastic pipe systems (note manufacturer's information and application limits). Complete tank cladding consisting of casing, cover and base panel. Equipped with signal anode and thermometer as standard. Cold water inlet pipe included, all-round orientation possible. Thermal insulation with minimal heat loss, directly foamed. Universal flange for dual circuit or single circuit operation with individually replaceable copper heating elements. The water in the storage tank is kept at the set temperature depending on the controller (depending on the selected connection). Infinitely variable temperature setting from approx. 35 degrees C to approx. 82 degrees C or temperature limitation of 45 degrees C to 60 degrees C possible. Controller-limiter combination with all-pole shutdown, automatic frost protection, rapid heating (once via built-in push button) also via remote control, switch for output variants. Quality and safety marks: VDE/GS mark, radio protection mark, IP24 (splash-proof)

YOUR ADVANTAGES

WORLDWIDE TRADE

Corporate video eibmarkt®


99% CUSTOMER SATISFACTION

> 500,000 customers worldwide


DHL TRACK & TRACE

Shipment tracking


COMPLAINTS HANDLING

Obliging and 100% safely


25 YEARS OF EXPERIENCE

In worldwide mail order


ORDER LIVE CHAT

With order history


SHORT DELIVERY TIME

Warehousing


REFUND

Within 14 days


DATA PROTECTION

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
 eibabo® electronics cheap online order
 eibabo® electric appliances buy online

